

Submit 3 Copies To Appropriate District Office
District I
1625 N French Dr , Hobbs, NM 88240
District II
1301 W Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd , Aztec, NM 87410
District IV
1220 S St Francis Dr , Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)		WELL API NO. 30-015-31338
1. Type of Well: Oil Well ☐ Gas Well ☒ Other		5. Indicate Type of Lease STATE ☒ FEE ☐
2. Name of Operator Devon Energy Production Co., LP		6. State Oil & Gas Lease No.
3. Address of Operator 20 North Broadway, OKC OK 73102-8260		7. Lease Name or Unit Agreement Name Scary Creek 25A State Com
4. Well Location Unit Letter <u>A</u> : <u>660</u> feet from the <u>North</u> line and <u>660</u> feet from the <u>West</u> line Section <u>25</u> Township <u>20S</u> Range <u>26E</u> NMPM Eddy County, NM		8. Well Number 1
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3264' GL		9. OGRID Number 6137
		10. Pool name or Wildcat Atoka

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENT=ION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: ATOKA COMPLETION ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

05/26/10 – 06/03/10:

MIRU. Tst anchors, bleed off pressure. Replace csg valves – RU WSU. ND WH, ld tbg w/22 bbl 2% KCl. POOH tbg & LD pkr. MIRU WL. Set CIBP @ 10,310', POOH WL. RIH dmp 35' cmt on top CIBP; new PBTD @ 10,275'. RIH & perf 9,740 – 9,748'; (3SPF) 24 holes. No pressure chg after perf. POOH RDMO WL. RIH & set pkr w/carbide trim to 9,710'. MIRU BJ srvs, pickle tbg w/500 gal rustbuster. ND BOP – NU WH. Land tbg under 13K compression. Swab. MIRU tree savor, frac equipmt. Set BS pop-off 1700 psi – tst lines 10K psi. Frac Atoka perfs @ 9,740 – 9,748 w/1,067 gal 7 1/2 % HCl, 13,775 gal xlinked fluid, 1,558 gal linear gel & 12,500# 20/40 carbolite. RDMO frac equip, tree savor. Swab. Turn well over to production.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE Sr. Staff Engineering Technician DATE 06/24/2010

Type or print name Stephanie A. Ysasaga E-mail address: Stephanie.Ysasaga@dmn.com PHONE: 405-552-7802

For State Use Only

APPROVED BY: [Signature] TITLE Dr. H. S. S. S. S. DATE 08/10/2010
Conditions of Approval (if any):



Weatherford

Company: Devon Energy

Well : State BQ #1

County & St.: Eddy New Mexico

Comments

Casing

Liner

Size 5 1/2"

Size

Weight 17#

Weight

Grade J-55

Grade

Lgth:

Lgth:

Packer set w/ 15,000# compression

Item

Description

ID

OD

Lgth.

Depth

KB

14'

1

263 jts 2 7/8" 8rd EUE N-80 tbg

2.441"

2.875"

8322.11'

8336.11'

1

2

5 1/2" x 2 7/8" T-2 on/off Tool w/ 2.31 F

Profile

2.313"

4.50"

1.81'

8337.92'

3

5 1/2" x 2 7/8" Arrowset 1-xx Tubing

Set Packer (w/ carbide slips)

2.375"

4.625"

6.96'

Top of Packer

8337.92'

Middle Element

8341.35'

Bottom of Packer

8344.88'

4

8' x 2 7/8" L-80 8rd tbg sub

2.441"

2.875"

8.06'

8349.41'

2

5

2 7/8" x 2.197" R profile landing nipple

2.197"

3.668"

.97'

8350.38'

3

4

5

Prepared For

Michael Palmer

Prepared By

Randy Frederick

Date

6/8/2010

Artesia, New Mexico

Office (575)746-8792

Cell (575)513-2271