#### Form 3160-5 (August 2007)


OCD-ARTESIA


UNITED STATES
DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No 1004-0137

Expires July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS  Do not use this form for proposals to drill or to re-enter an abandoned well Use Form 3160-3 (APD) for such proposals				5 Lease Senal No NM-86241 6 If Indian, Allottee or Tribe Name NA 7 If Unit or CA/Agreement, Name and/or No		
SUBMIT IN TRIPLICATE - Other instructions on page 2.						
1 Type of Well  Oil Well  X Gas Well Other				NMNM100714		
				8 Well Name and No		
2 Name of Operator				Hill View AHE Federal Com #4		
Yates Petroleum Corporation				9 API Well No	,	
3a Address	one No (include area co					
105 S 4th Str., Artesia, NM 88210 575-748-1471  4 Location of Well (Footage, Sec , T , R ,M , OR Survey Description)				10 Field and Pool of		
4 Location of Well (Foolage, Sec., F., N., III., ON Survey Description)				Cemetary; Wolfcamp  11 County or Parish, State		
1980'FSL & 1980'FEL of Section 23-T20S-R24E (Unit J, NWSE)				Eddy County, New Mexico		
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, RI						
TYPE OF SUBMISSION TYPE OF ACTION				<del></del>		
	Acidize	Deepen	Production (	Start/Resume)	Water Shut-Off	
Notice of Intent	Alter Casing	Fracture Treat	Reclamation		Well Integrity	
	Casing Repair	New Construction	Recomplete		Other	
Notice of Intent Subsequent Report		<del>,  </del>				
Change Plans X Plug and Abandon			Temporarily	Temporanly Abandon		
Final Abandonment Notice	Convert to Injection	Plug Back	Water Dispo	sal		
Attach the Bond under which the work will be following completion of the involved operations testing has been completed. Final Abandonmer determined that the site is ready for final inspect.  Yates Petroleum Corporation pl. 1. MIRU WSU. Rig up any safe. 2. Set a CIBP at 7358' with 35' of 3. Spot a 30 sx Class "C" ceme. 4. Spot a 30 sx Class "C" ceme. 5. Spot a 30 sx Class "C" ceme. 6. Spot a 30 sx Class "C" ceme. 7. Spot a 30 sx Class "C" ceme. 8. Remove all surface equipment. NOTE: Yates Petroleum Corporation 14. Thereby certify that the foregoing is true and the strength of the strength of the surface.	If the operation results in a multiple control Notices must be filed only after all requision.  It and to plug and abandon ety equipment as needed cement on top.  Int plug from 5408'-5964'.  Int plug from 3322'-3482'.  Int plug from 1977'-2157'.  Int plug from 0'-150' across the and weld dry hole mark atton will use steel pits and needed.	npletion or recompletion in a irrements, including reclamate this well as follow. No casing recover This will put a 16 This will put a 16 across surface cases surface of the occurrence of the occurrence as per regulat	new interval, a Form 3' ion, have been complete.  WES: Very will be attempted across 60' plug across 60' plug across asing shoe Western Western Western Western SEE	LAMATION PROC ATTACHED empted. TOH s the Wolfcamp B Bone Spring G Glorieta top. OC 3 hrs and and reset if ne	SEP 1 3 20 CEDURINMOCD ART with tubing p top. top. tag plug. Reset	
Name (Printed/Typed)						
Tina Hu	erta	Title Regu	latory Complia	nce Superviso	<u>ir                                     </u>	
Signature ( \lambda \tag{\tag{\tag{V}}	uerta	Date July 2	29, 2 <b>010</b>	DDDAVIT		
	THIS SPACE FOR FE	DERAL OR STATE	OFFICE USE	ILLUAF	И	
Approved by  Conditions of approval, if any are attached certify that the applicant holds legal or equit which would entitle the applicant to conduct of Title 18 U.S.C. Section 1001 and Title 43 U.S. any false, fictitious or fraudulent statements of	table title to those rights in the sub- operations thereon	ject lease Office	/\$/ D and willfully to make the	SEP 8 2010 UST WINK SEP 8 2010 UST WINK SEP 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	agency of the United States	
(Instructions on page 2)				CILLD OLL	IUL	





Yates Petroleum Corporation

NM-86241: Hill View AHE Federal Com #4

API: 30-015-26356

Eddy County, New Mexico

RE: Plugging and Abandonment Requirements, Conditions of Approval

H2S monitoring equipment is to be on site. All plugs to be a minimum 25sx.

- 1. OK
- 2. OK (Perfs)
- 3. WOC and tag at 5542' or shallower Otherwise OK (Wolfcamp DV Tool)
- 4. OK (Bone Spring)
- 5. OK (Glorietta)
- 6. OK (Casing shoe)
- 7. Plug to run from 400' to surface Otherwise OK (Cave/Karst Surface)
- 8. Verify Cement to surface in all annuluses Otherwise OK.
- 9. Submit a subsequent report to the BLM.

See attached standard COAs.

DHW 083110

### BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

## Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90<sup>th</sup> day provide this office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.
- 5. Cement Requirement: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. In lieu of a cement plug in a cased hole, a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Any plug that requires a tag will have a minimum WOC time of 4 hours.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class. "C", for up to 7,500 feet of depth or Neat Class. "H", for deeper than 7,500 feet plugs.

- 6. <u>Dry Hole Marker</u>: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). **The BLM is to be notified when the wellhead is cut off to verify that cement is to surface in the casing and all annuluses.** The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement. The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).
- 7. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and five copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation procedure.

DHW 112309



# **United States Department of the Interior**

### **BUREAU OF LAND MANAGEMENT**

Carlsbad Field Office 620 E Greene St Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

## **Reclamation Objectives and Procedures**

**Reclamation Objective:** Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its pre-disturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines. Strip and remove caliche, contour the location to blend with the surrounding landscape, re-distribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

1. The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.

- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.
- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Environmental Protection Specialist 575-234-5909, 575-361-2648 (Cell)

Terry Gregston Environmental Protection Specialist 575-234-5958

Bobby Ballard Environmental Protection Specialist 575-234-2230

Randy Rust Natural Resource Specialist 575-234-5943

Linda Denniston Environmental Protection Specialist 575-234-5974

Jennifer Van Curen Environmental Protection Specialist 575-234-5905

Justin Frye Environmental Protection Specialist 575-234-5922

5

Cody Layton Natural Resource Specialist 575-234-5959

Trishia Bad Bear Natural Resource Specialist 575-393-3612

Todd Suter Surface Protection Specialist 575-234-5987

Doug Hoag Civil Engineering Technician 575-234-5979

Tanner Nygren Natural Resource Specialist 575-234-5975

John Fast Natural Resource Specialist 575-2345996