## OCD-ARTESIA



(Instructions on page 2)

#### **UNITED STATES** DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

	FORM APPROVED OMB No 1004-0137 Expires July 31, 2010
5 Lease Serial No.	

SUNDRY NOTICES	LAND RI	FPORTS	ON WELL	ç

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

	Expires July 31, 2010	,
5 Lease Serial No. LC - 070286		
6. If Indian, Allotte	e or Tribe Name	

SUBMI	T IN TRIPLICATE – Other inst			7 If Unit of CA/Agree	ement, Name and/or No.
1 Type of Well		RECEIVE	EDT		
Oil Well Gas V	Vell Other	OCT 1 = 20		8 Well Name and No	<b>ጋ</b> ሬ Federal #6
2 Name of Operator Hudson Oil Company of Texas		OCT 15 201	ŀ	9. API Well No 30-015-0472	2
3a Address 616 Texas Street Fort Worth, Texas 76102	3b 817	-336-7109	SIA	10 Field and Pool or E Dos Hermanos/Yate	•
4. Location of Well (Footage, Sec., T.,				11 Country or Parish,	State
660' FNL & 660' FWL, Unit D, Sec. 33, Townsh	p 20 South, Range 30 East			Eddy County, New N	Mexico
12. CHEC	CK THE APPROPRIATE BOX(E	S) TO INDICATE NATUR	E OF NOTI	CE, REPORT OR OTHE	ER DATA
TYPE OF SUBMISSION	,	Т	PE OF AC	ΓΙΟΝ	
✓ Notice of Intent	Acidize Alter Casing	Deepen Fracture Treat	=	duction (Start/Resume)	Water Shut-Off Well Integrity
Subsequent Report	Casing Repair	New Construction	Rec	omplete	Other
Subsequent Report	Change Plans	Plug and Abandon	Tem	porarily Abandon	
Final Abandonment Notice	Convert to Injection	Plug Back	☐ Wat	er Disposal	
be established, spot cement 50	185' - 1305'. A minimum of 12i below perfs and raise cemer shoe from 427' - 595' A minir ment 50' below perfs and perfo of 60'. Verify cement to surfac	at to 1185' or shallower.  The state of 168' in length (Minorm a 2nd attempt 10' above in all annuluses at cut of the state of the stat	imum of 40 ove tag. off.	Sex). WOC and tag at	-
RECLA	MATION PROCEDURE ATTACHED	CO	NDITI	ONS OF API	PROVAL
14 I hereby certify that the foregoing is t	rue and correct Name (Printed/Typ	ned)			
E. Randall Hudson III		Title Geologis	st		
Signature Signature		Date 09/30/20	010		
	THIS SPACE FO	REDERAL OR ST	ATE OF	FARBROVE	n l
Approved by  Conditions of approval. If any, are attached that the applicant holds legal or equitable tentitle the applicant to conduct operations  Title 18 U S C Section 1001 and Title 43 fictitious or fraudulent statements or repre	ttle to those rights in the subject least thereon.	se which would Office		OCT 1 4 2000 OCT 1 DUSTIN WINK	
mentious of transmittent statements of repre	semations as to any matter within it	s jurisdiction		ALMIEDOUD LIFTD OL	IIVL



#### **VELL COMPLETION SKETCH**

Proposed Wellbore

9/10/2010

ELL	COMPLETION SKETCH	Proposed Wellbore	9/10/2010
F	ederal #6	Dos Hermandos Y-SR	Eddy County, New Mexico
	PRESENT COMPLETION	☑ RECOMMENDED COMPLETION	API# 30-015-04721
	PERMANENT WELL BORE DATA		DATA ON THIS COMPLETION
	Transcription of the second of	1	
le	History:		
	Spudded	<b>,</b> , , , , , , , , , , , , , , , , , ,	
	660' FNL & 660' FWL		
	Sec 33 - T20S - R30E		60' Surface plug.
	GL = 3353'		· •
	LC-070286		
·			
	•		
	•		
	8 5/8* 24# @ 487'		
	Cmt w/ 150 sx sx H.		
	Circ cmt to surface		
	Top of Salt @ 545'		
	10p of Oak (@ 3-10		C
			Cement plug 427' - 595'
	Base of Salt @ 1255		
	base of Salt @ 1255		_
			Cement plug 1185' - 1305'
	Top of Value @ 44201		
	Top of Yates @ 1436'		
		27,7	25 sx Cement plug
	8 1/4° Hole		25 sx Cement plug CIBP @ 1571'
	7° 20# @ 1596°		-
	Cmt w/ 275 sx		
	Cmt to surface	i i	
	One to Sungoe	Į l	
		į į	
		!!!	
		1 1	
		i i	

Hudson Oil Company of Texas NMLC-070286: Federal 26 #6

API: 30-015-04722

Eddy County, New Mexico

RE: Plugging and Abandonment Requirements, Conditions of Approval

- 1. Move: Set CIBP at 1540' Otherwise OK (Open hole Yates)
- 2. Due to R-111-P Potash, a solid cement plug is required across the entire salt section. Perf at 1305' and squeeze a plug to 437' (multiple plugs due to well conditions is OK). WOC and tag at 437' or shallower. If injection rate cannot be established, spot 25sx below perfs, WOC and tag, perf above tag, and attempt again. Repeat until injection rate is established. (Yates Salt/R-111-P Potash Casing shoe)
- 3. REMOVED: Covered in previous step.
- 4. Perforations will be required. Fill in casing/annuluses as required Otherwise OK (Surface)
- 5. OK

H<sub>2</sub>S monitoring equipment shall be on location.

See attached standard COAs.

DHW 101410

### BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

## Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90<sup>th</sup> day provide this office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.
- 5. Cement Requirement: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. In lieu of a cement plug in a cased hole, a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Any plug that requires a tag will have a minimum WOC time of 4 hours.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

- 6. <u>Dry Hole Marker</u>: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). **The BLM is to be notified when the wellhead is cut off to verify that cement is to surface in the casing and all annuluses.** The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement. The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).
- 7. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and five copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation procedure.

DHW 112309



# **United States Department of the Interior**

#### **BUREAU OF LAND MANAGEMENT**

Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm gov/nm



In Reply Refer To: 1310

## **Reclamation Objectives and Procedures**

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its pre-disturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines. Strip and remove caliche, contour the location to blend with the surrounding landscape, re-distribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

1. The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.

- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.
- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Environmental Protection Specialist 575-234-5909, 575-361-2648 (Cell)

Terry Gregston Environmental Protection Specialist 575-234-5958

Bobby Ballard Environmental Protection Specialist 575-234-2230

Randy Rust Natural Resource Specialist 575-234-5943

Linda Denniston Environmental Protection Specialist 575-234-5974

Jennifer Van Curen Environmental Protection Specialist 575-234-5905

Justin Frye Environmental Protection Specialist 575-234-5922 Cody Layton Natural Resource Specialist 575-234-5959

Trishia Bad Bear Natural Resource Specialist 575-393-3612

Todd Suter Surface Protection Specialist 575-234-5987

Doug Hoag Civil Engineering Technician 575-234-5979

Tanner Nygren Natural Resource Specialist 575-234-5975

John Fast Natural Resource Specialist 575-2345996