State of New Mexico		Form C-103	
District I Energy, Minerals and I	Energy, Minerals and Natural Resources N. French Dr., Hobbs, NM 88240 WELL API NO.		October 13, 2009
1625 N. French Dr., Hobbs, NM 88240	-		
1301 W. Grand Ave., Artesia, NM 88210 OIL CONSERVAT			ė
1000 Rio Brazos Rd Aztec NM 87410	O Rio Brazos Pd Artes NM 97410] FEE
District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505	Santa Fe, NM 8/303		No.
SUNDRY NOTICES AND REPORTS ON WELLS		7. Lease Name or Unit A	greement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH		Allied State	
PROPOSALS.) 1. Type of Well: Oil Well Gas Well Other		8. Well Number	
2. Name of Operator		9. OGRID Number	
Mewbourne Oil Company		14744	
3. Address of Operator PO Box 5270, Hobbs, NM 88241		10. Pool name or Wildca Penlon; Bone Springs	70920
4. Well Location		Training prints	
Unit Letter_M:660'_feet from the _South	line and _660'	feet from the _W	estline
Section 22 Township 20S	Range 27E	NMPM Eddy	County
11. Elevation (Show whether 3261' GL	DR, RKB, RT, GR, etc.,		
3201 QL			
12. Check Appropriate Box to Indicate	e Nature of Notice,	Report or Other Data	
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:			OF:
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐			ING CASING 🗌
TEMPORARILY ABANDON			Α 🗆
PULL OR ALTER CASING MULTIPLE COMPL	CASING/CEMEN	T JOB 🔲	
DOWNHOLE COMMINGLE			
OTHER:		letion Sundry	×
13. Describe proposed or completed operations. (Clearly state	all pertinent details, an	d give pertinent dates, inclu	ding estimated date
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.			
09/29/10 RIH w/5 ½" 10k CIBP & set @ 10705'. Dumped 50' cement on plug. PBTD @ 9800'			
09/30/10 Perforate Bone Springs @ 7942' to 7964' (22', 44 holes, 2 SPF, 0.38 EHD) Frac w/1000 gals 15% HCl & 50,000 gals Viking			
3000 X-linked gel w/80,000# 20/40 White Sand & 20,000 Super LC 20/40 sand.			
10/01/10 Perforate Bone Springs @ 6538' to 6558' (20', 20 holes, 1 SPF, 0.38 EHD) & 6449' to 6464' (15', 15 holes, 1SPF, 0.38" EHD).			
Frac 6449' to 6558' w/2000 gals 15% HCl & 110,000 gals Viking 3000 X-linked gel w/180,000# 20/40 White Sand & 20,000 Super LC			
20/40 sand.			
10/02/10 Flowback for cleanup.		REC	EIVED
10/06/10 RIH w/2 %" 6.5# N-80 tbg to 8065'.		OCT	28 2010
10/08/10 RIH w/pump & rods to 7987'. PWOL.		NMOCE	ARTESIA
I hereby certify that the information above is true and complete to the best of my knowledge and belief.			
SIGNATURE Jackie Lathan TITLE H	obbs Regulatory	DATE 10/	22/10
For State Use Only	ldress: jlathan@mewbo		575-393-5905
APPROVED BY: Double Wray TITLE FO Conditions of Approval (if any): PA Avalor	eld Supervisor	DATE 10)-29-11)
Conditions of Approval (if any):	N	م م	/
1714 Hualon 1	10110W CO	oH5>	,

- -