

Submit 1 Copy To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
October 13, 2009

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-38005
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. L-3355
7. Lease Name or Unit Agreement Name Parkway 26 State Com
8. Well Number 3H
9. OGRID Number 14744
10. Pool name or Wildcat Turkey Track Bone Spring 60660
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3325' GL

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Mewbourne Oil Company

3. Address of Operator
PO Box 5270, Hobbs, NM 88241

4. Well Location
Unit Letter E : 2240' feet from the North line and 330' feet from the West line
Section 26 Township 19S Range 29E NMPM Eddy County

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

10/15/10...TD 12 1/4" hole at 3315'. Ran 3315' 9 5/8" 36/40# J55 LT & C csg. Cemented with 180 sks Thixad Class H w/additives. Mixed @ 14.6 #/g w/ 1.52 yd. Followed w/200 sks BJ Lite Class C (35:65:6) w/additives. Mixed @ 12.5#/g w/2.05 yd. Followed w/700 sks Lite C (50:50:10) w/additives. Mixed @ 11.7#/g w/2.53 yd. Tail w/200 sks Class C w/2% CaCl2. Mixed @ 14.8 #/g w/ 1.34 yd. Plug down @ 8:30 am 10/15/10. Circulated 100 sks to pit. At 10:15 am, 10/16/10 tested csg & BOPE to 1500#. Drilled out with 8 3/4" bit.

10/29/10...TD'ed 8 3/4" hole @ 8426'. Ran 8426' 7" 26# P110 BT&C/LT&C Csg. Cemented with 700 sks Class "H" (50:50:10) with additives. Mixed @ 11.7 /g w/ 2.54 yd. Tail with 400 sks Class "H" w/additives. Mixed @ 15.6 #/g w/ 1.18 yd. Plug down @ 4:45 pm 10/29/10. Circ 93 sks cmt to pit. At 12:30 pm on 10/31/10 tested BOPE and casing to 1500# for 30 minutes, held OK. Drilled out with 6 1/8" bit.

Spud Date: 10/05/10

Rig Release Date:

RECEIVED

NOV 22 2010

NMOCD ARTESIA

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 11/15/10

Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905

For State Use Only

APPROVED BY: David Gray TITLE Field Supervisor DATE 11-24-10
Conditions of Approval (if any):

Cat