Submit 1 Copy To Appropriate District	Control of the contro	F 0.102
Office District I	State of New Mexico Energy, Minerals and Natural Resources	Form C-103 October 13, 2009
1625 N. French Dr., Hobbs, NM 88240 District II	Energy, Timerals and Tracarat Recognition	WELL API NO.
1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION DIVISION	30-015-22435 5. Indicate Type of Lease
<u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Francis Dr.	STATE FEE
District IV 1220 S. St. Francis Dr., Santa Fe, NM	Santa Fe, NM 87505	6. State Oil & Gas Lease No.
87505 SUNDRY NOTE	CES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
	SALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A CATION FOR PERMIT" (FORM C-101) FOR SUCH	NDDUP Unit 8. Well Number
	Gas Well Other P&A	114
2. Name of Operator Yates Petroleum Corporation		9. OGRID Number 025575
3. Address of Operator	14 00010	10. Pool name or Wildcat
105 South Fourth Street, Artesia, N 4. Well Location	M 88210	Dagger Draw; Upper Penn, North
1	1980 feet from the North line and	1980 feet from the West line
Section 28	Township 19S Range 25E	NMPM Eddy County
	11. Elevation (Show whether DR, RKB, RT, GR, etc. 3502'KB	
Can provide the second control of the second		
12. Check A	appropriate Box to Indicate Nature of Notice	, Report or Other Data
NOTICE OF IN		BSEQUENT REPORT OF:
PERFORM REMEDIAL WORK TEMPORARILY ABANDON	PLUG AND ABANDON REMEDIAL WOI CHANGE PLANS COMMENCE DF	RK ☐ ALTERING CASING ☐ ☐ RILLING OPNS.☐ PANDA ☒
PULL OR ALTER CASING	MULTIPLE COMPL CASING/CEMEN	
DOWNHOLE COMMINGLE		
OTHER:	☐ OTHER:	
	leted operations. (Clearly state all pertinent details, and rk). SEE RULE 19.15.7.14 NMAC. For Multiple Co	
proposed completion or reco		empression in the same and analysis and a
2/8/11 - ND wellhead. NU BOP. S	et 5-1/2" CIBP at 7590'.	
2/9/11 - Loaded hole w/ salt gel. Tes	sted casing to 600 psi. Spotted 20 sx "H" neat cemen	
4 holes at 6022'. Pressured up to 600 psi. TIH to 6072'. Spotted 30 sx "C" neat cement 1.32 yield, 14.8 ppg. WOC. 2/10/11 - Tagged plug at 5800'. Perforated 4 holes at 4022'. Packer at 3553'. Pumped 50 sx "C" neat cement. WOC. Tagged at 3812'		
Perforated 4 holes at 2368'. Packer at 1905'. Pumped 50 sx "C" neat cement. WOC.		
	forated 4 holes at 1230' Set packer at 710'. Pumped Pumped down 5-1/2", circulated out 8-5/8" x 5-1/2'	
surface. ND BOP.		
WELL IS PLUGGED AND ABAN	wellhead. Installed dry hole marker. Filled cellar and IDONED.	
		RECEIVED
		FEB 23 2011
		NMOCD ARTESIA
Spud Date:	Rig Release Date:	
I hereby certify that the information	above is true and complete to the best of my knowled	ge and belief.
SIGNATURE (TITLE Regulatory Complianc	e Technician DATE <u>February 22, 2011</u>
Type or print name Craig Ato	on E-mail address:caton@vatespetroleu	m.com PH ONE: 575-748-4385
For State Use Only	Approved for plugging of well Liability under bond is retaine	d pending receipt
APPROVED BY	TITLE of C-103 (Subsequent Report of which may be found at OCD W	of Well Plugging) Veb Page under DATE 2/23/20//
Conditions of Approval (if any):	Forms, www.cmnrd.state.nm.u	