| Office | District | State of New Mexico | 0 | | Form C-103 |
|--|--|---|---|--|--|
| District I | Energy, 1 | Minerals and Natural I | Resources _r | | October 13, 2009 |
| 1625 N. French Dr., Hobbs, NM | 1 88240 | | | WELL API NO. | |
| District II 1301 W. Grand Ave., Artesia, N | M 88210 OIL CO | ONSERVATION DI | VISION | 30-015-37537 5. Indicate Type of Leas | `A |
| District III | 123 | 20 South St. Francis | Dr. | STATE STATE | FEE |
| 1000 Rio Brazos Rd., Aztec, NN District IV | И 87410 | Santa Fe, NM 87505 | 5 | 6. State Oil & Gas Lease | ···· |
| 1220 S. St. Francis Dr., Santa Fe 87505 | | | | V-7317 | |
| SUNDRY NOTICES AND REPORTS ON WELLS | | | | 7. Lease Name or Unit A | Agreement Name |
| (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A | | | | Maduro BOZ State 🗸 | _ |
| DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) | | | JCH | 8. Well Number | |
| 1. Type of Well: Oil Well Gas Well Other | | | | 1H | |
| 2. Name of Operator | | | | 9. OGRID Number | |
| Yates Petroleum Corporation | | | | 025575 | |
| 3. Address of Operator | | | | 10. Pool name or Wildcat | |
| 105 South Fourth Street, Artesia, NM 88210 | | | | Wildcat; Bone Spring | |
| 4. Well Location Unit Letter P | : 660 feet fro | om the South | line and | feet from the | East line |
| Section | 10 Towns | hip 25S Range | 27E | NMPM Eddy | County |
| Section | | (Show whether DR, RK | | | County |
| | 11. Die vation | 3178'GR | <i>D</i> , <i>R</i> 1, <i>GR</i> , <i>cic.</i>) | 光 有 3 | 相 加 数 |
| | PAGE 1 | | | | |
| 12. | Check Appropriate E | Box to Indicate Natur | re of Notice, l | Report or Other Data | |
| NOTICE | OF INTENTION T | TO: 1 | QI ID | SEQUENT REPOR | T OE: |
| PERFORM REMEDIAL W | | | SOD: MEDIAL WORK | | TOF. RING CASING □ |
| TEMPORARILY ABANDO | | | | LLING OPNS. P AND | |
| PULL OR ALTER CASING | | | ASING/CEMENT | | |
| DOWNHOLE COMMINGL | | 0 0 | ion to localization | | |
| | | | | | |
| | | | | | |
| OTHER: | | | THER: Producti | | \boxtimes |
| 13. Describe proposed | | s. (Clearly state all perti | nent details, and | I give pertinent dates, inclu | uding estimated date |
| 13. Describe proposed of starting any pro | posed work). SEE RUL | s. (Clearly state all perti | nent details, and | | uding estimated date |
| 13. Describe proposed of starting any pro | | s. (Clearly state all perti | nent details, and | I give pertinent dates, inclu | uding estimated date |
| 13. Describe proposed of starting any pro proposed completi | posed work). SEE RUL ion or recompletion. | s. (Clearly state all perti E 19.15.7.14 NMAC. F | nent details, and or Multiple Con | I give pertinent dates, inclu inpletions: Attach wellbord | uding estimated date |
| 13. Describe proposed of starting any proproposed complete 2/11/11 – Dilled to 8546' a | oposed work). SEE RUL ion or recompletion. Indicate the reduced hole to 7-7/8 | s. (Clearly state all perti E 19.15.7.14 NMAC. F | nent details, and or Multiple Con | I give pertinent dates, inclu inpletions: Attach wellbord | uding estimated date |
| 13. Describe proposed of starting any proproposed complete 2/11/11 – Dilled to 8546' a 2/20/11 – Reached TD 7-7/2/21/11 – Set 5-1/2" 17#, 2 | oposed work). SEE RUL ion or recompletion. and reduced hole to 7-7/8' '8" hole to 12,550'. 10# N-80 P-110 LT&C ca | s. (Clearly state all perti E 19.15.7.14 NMAC. F "and resumed drilling d asing at 12,550'. DV too | nent details, and or Multiple Con irectionally. KO | I give pertinent dates, inclunded in pletions: Attach wellbord DP at 7642'. At collar at 12,457'. Ceme | uding estimated date e diagram of |
| 13. Describe proposed of starting any proposed complete 2/11/11 – Dilled to 8546' a 2/20/11 – Reached TD 7-7/2/21/11 – Set 5-1/2" 17#, 2 625 sx 35:65:6 Poz "C" + 1 | posed work). SEE RUL ion or recompletion. and reduced hole to 7-7/8'/8" hole to 12,550'. 0# N-80 P-110 LT&C ca 1% D112 + 0.125#/sx D1 | s. (Clearly state all perting E 19.15.7.14 NMAC. F "and resumed drilling dasing at 12,550". DV too 30 + 0.015g/sx D177 + | nent details, and or Multiple Con irectionally. KC ol at 4793'. Floa 6% D20 + 2#/sx | I give pertinent dates, inclunded proposed propo | uding estimated date e diagram of ented stage 1 with 046 + 0.1% D800 |
| 13. Describe proposed of starting any proposed complete 2/11/11 – Dilled to 8546' a 2/20/11 – Reached TD 7-7/2/21/11 – Set 5-1/2" 17#, 2 625 sx 35:65:6 Poz "C" + 1 (yld 2.08, wt 12.6). Tailed | posed work). SEE RUL ion or recompletion. and reduced hole to 7-7/8'/8" hole to 12,550'. 0# N-80 P-110 LT&C ca 1% D112 + 0.125#/sx D1 in with 600 sx PVL + 0. | s. (Clearly state all perting E 19.15.7.14 NMAC. F "and resumed drilling dasing at 12,550". DV too 30 + 0.015g/sx D177 + 6 5% D112 + 30% D151 + | nent details, and or Multiple Con irectionally. KC of at 4793'. Floa 6% D20 + 2#/sx - 1.5% D174 + 6 | I give pertinent dates, include pletions: Attach wellbord DP at 7642'. at collar at 12,457'. Ceme at D42 + 5% D44 + 0.2% D0.035g/sx D177 + 0.2% D4.000000000000000000000000000000000000 | uding estimated date e diagram of ented stage 1 with 046 + 0.1% D800 46 + 0.5% D79 + |
| 13. Describe proposed of starting any proproposed complete 2/11/11 – Dilled to 8546' a 2/20/11 – Reached TD 7-7/2/21/11 – Set 5-1/2" 17#, 2 625 sx 35:65:6 Poz "C" + 1 (yld 2.08, wt 12.6). Tailed 0.8% D800 (yld 1.83, wt 13 | posed work). SEE RUL ion or recompletion. and reduced hole to 7-7/8'/8" hole to 12,550". 10# N-80 P-110 LT&C ca 10% D112 + 0.125#/sx D1 in with 600 sx PVL + 0. 3). Circulated 215 sx to | s. (Clearly state all perting E 19.15.7.14 NMAC. F "and resumed drilling d asing at 12,550". DV too 30 + 0.015g/sx D177 + 6 5% D112 + 30% D151 + pit. Cemented stage 2 w | nent details, and or Multiple Con irectionally. KC of at 4793'. Floa 6% D20 + 2#/sx - 1.5% D174 + 0 ith 470 sx 35:65 | I give pertinent dates, include pletions: Attach wellbord DP at 7642'. at collar at 12,457'. Ceme at D42 + 5% D44 + 0.2% D0.035g/sx D177 + 0.2% D45:6 Poz "C" + 1% D112 + | uding estimated date e diagram of ented stage 1 with 046 + 0.1% D800 46 + 0.5% D79 + 0.125#/sx D130 + |
| 13. Describe proposed of starting any proproposed complete 2/11/11 – Dilled to 8546' a 2/20/11 – Reached TD 7-7/2/21/11 – Set 5-1/2" 17#, 2 625 sx 35:65:6 Poz "C" + 1 (yld 2.08, wt 12.6). Tailed 0.8% D800 (yld 1.83, wt 13.6% D20 + 2#/sx D42 + 5% | posed work). SEE RUL ion or recompletion. and reduced hole to 7-7/8'/8" hole to 12,550". 10# N-80 P-110 LT&C ca 10% D112 + 0.125#/sx D1 in with 600 sx PVL + 0. 3). Circulated 215 sx to | s. (Clearly state all perting E 19.15.7.14 NMAC. F "and resumed drilling d asing at 12,550". DV too 30 + 0.015g/sx D177 + 6 5% D112 + 30% D151 + pit. Cemented stage 2 w | nent details, and or Multiple Con irectionally. KC of at 4793'. Floa 6% D20 + 2#/sx - 1.5% D174 + 0 ith 470 sx 35:65 | I give pertinent dates, include pletions: Attach wellbord DP at 7642'. at collar at 12,457'. Ceme at D42 + 5% D44 + 0.2% D0.035g/sx D177 + 0.2% D45:6 Poz "C" + 1% D112 + | uding estimated date e diagram of ented stage 1 with 046 + 0.1% D800 46 + 0.5% D79 + 0.125#/sx D130 + |
| 13. Describe proposed of starting any proproposed complete 2/11/11 – Dilled to 8546' a 2/20/11 – Reached TD 7-7/2/21/11 – Set 5-1/2" 17#, 2 625 sx 35:65:6 Poz "C" + 1 (yld 2.08, wt 12.6). Tailed 0.8% D800 (yld 1.83, wt 13 | posed work). SEE RUL ion or recompletion. and reduced hole to 7-7/8'/8" hole to 12,550". 10# N-80 P-110 LT&C ca 10% D112 + 0.125#/sx D1 in with 600 sx PVL + 0. 3). Circulated 215 sx to | s. (Clearly state all perting E 19.15.7.14 NMAC. F "and resumed drilling d asing at 12,550". DV too 30 + 0.015g/sx D177 + 6 5% D112 + 30% D151 + pit. Cemented stage 2 w | nent details, and or Multiple Con irectionally. KC of at 4793'. Floa 6% D20 + 2#/sx - 1.5% D174 + 0 ith 470 sx 35:65 | I give pertinent dates, include pletions: Attach wellbord of the properties of the p | uding estimated date e diagram of ented stage 1 with 046 + 0.1% D800 46 + 0.5% D79 + 0.125#/sx D130 + |
| 13. Describe proposed of starting any proproposed complete 2/11/11 – Dilled to 8546' a 2/20/11 – Reached TD 7-7/2/21/11 – Set 5-1/2" 17#, 2 625 sx 35:65:6 Poz "C" + 1 (yld 2.08, wt 12.6). Tailed 0.8% D800 (yld 1.83, wt 13.6% D20 + 2#/sx D42 + 5% | posed work). SEE RUL ion or recompletion. and reduced hole to 7-7/8'/8" hole to 12,550". 10# N-80 P-110 LT&C ca 10% D112 + 0.125#/sx D1 in with 600 sx PVL + 0. 3). Circulated 215 sx to | s. (Clearly state all perting E 19.15.7.14 NMAC. F "and resumed drilling d asing at 12,550". DV too 30 + 0.015g/sx D177 + 6 5% D112 + 30% D151 + pit. Cemented stage 2 w | nent details, and or Multiple Con irectionally. KC of at 4793'. Floa 6% D20 + 2#/sx - 1.5% D174 + 0 ith 470 sx 35:65 | DP at 7642'. at collar at 12,457'. Ceme D42 + 5% D44 + 0.2% D5:6 Poz "C" + 1% D112 + with 100 sx Class "C" + 0. | uding estimated date e diagram of ented stage 1 with 046 + 0.1% D800 46 + 0.5% D79 + 0.125#/sx D130 + |
| 13. Describe proposed of starting any proproposed complete 2/11/11 – Dilled to 8546' a 2/20/11 – Reached TD 7-7/2/21/11 – Set 5-1/2" 17#, 2 625 sx 35:65:6 Poz "C" + 1 (yld 2.08, wt 12.6). Tailed 0.8% D800 (yld 1.83, wt 13.6% D20 + 2#/sx D42 + 5% | posed work). SEE RUL ion or recompletion. and reduced hole to 7-7/8'/8" hole to 12,550". 10# N-80 P-110 LT&C ca 10% D112 + 0.125#/sx D1 in with 600 sx PVL + 0. 3). Circulated 215 sx to | s. (Clearly state all perting E 19.15.7.14 NMAC. F "and resumed drilling d asing at 12,550". DV too 30 + 0.015g/sx D177 + 6 5% D112 + 30% D151 + pit. Cemented stage 2 w | nent details, and or Multiple Con irectionally. KC of at 4793'. Floa 6% D20 + 2#/sx - 1.5% D174 + 0 ith 470 sx 35:65 | I give pertinent dates, include pletions: Attach wellbord of the properties of the p | uding estimated date e diagram of ented stage 1 with 046 + 0.1% D800 46 + 0.5% D79 + 0.125#/sx D130 + |
| 13. Describe proposed of starting any proproposed complete 2/11/11 – Dilled to 8546' a 2/20/11 – Reached TD 7-7/2/21/11 – Set 5-1/2" 17#, 2 625 sx 35:65:6 Poz "C" + 1 (yld 2.08, wt 12.6). Tailed 0.8% D800 (yld 1.83, wt 13.6% D20 + 2#/sx D42 + 5% | posed work). SEE RUL ion or recompletion. and reduced hole to 7-7/8'/8" hole to 12,550". 10# N-80 P-110 LT&C ca 10% D112 + 0.125#/sx D1 in with 600 sx PVL + 0. 3). Circulated 215 sx to | s. (Clearly state all perting E 19.15.7.14 NMAC. F "and resumed drilling d asing at 12,550". DV too 30 + 0.015g/sx D177 + 6 5% D112 + 30% D151 + pit. Cemented stage 2 w | nent details, and or Multiple Con irectionally. KC of at 4793'. Floa 6% D20 + 2#/sx - 1.5% D174 + 0 ith 470 sx 35:65 | DP at 7642'. at collar at 12,457'. Ceme to D42 + 5% D44 + 0.2% D0.035g/sx D177 + 0.2% D0.0 | uding estimated date e diagram of ented stage 1 with 046 + 0.1% D800 46 + 0.5% D79 + 0.125#/sx D130 + 2% D13 (yld 1.33, |
| 13. Describe proposed of starting any proposed complete 2/11/11 – Dilled to 8546' a 2/20/11 – Reached TD 7-7/2/21/11 – Set 5-1/2" 17#, 2 625 sx 35:65:6 Poz "C" + 1 (yld 2.08, wt 12.6). Tailed 0.8% D800 (yld 1.83, wt 13.6% D20 + 2#/sx D42 + 5% wt 14.8). | posed work). SEE RUL ion or recompletion. Ind reduced hole to 7-7/8'/8" hole to 12,550'. Ind reduced hole to 7-7/8' Ind reduced hole to | s. (Clearly state all perting E 19.15.7.14 NMAC. F "and resumed drilling d asing at 12,550". DV too 30 + 0.015g/sx D177 + 6 5% D112 + 30% D151 + pit. Cemented stage 2 w 6% D800 (yld 2.08, wt 12) | nent details, and or Multiple Conditionally. KC of at 4793'. Floa 6% D20 + 2#/sx - 1.5% D174 + (ath 470 sx 35:65). Tailed in v | DP at 7642'. at collar at 12,457'. Ceme to D42 + 5% D44 + 0.2% D0.035g/sx D177 + 0.2% D0.0 | uding estimated date e diagram of ented stage 1 with 046 + 0.1% D800 46 + 0.5% D79 + 0.125#/sx D130 + 2% D13 (yld 1.33, |
| 13. Describe proposed of starting any proproposed complete 2/11/11 – Dilled to 8546' a 2/20/11 – Reached TD 7-7/2/21/11 – Set 5-1/2" 17#, 2 625 sx 35:65:6 Poz "C" + 1 (yld 2.08, wt 12.6). Tailed 0.8% D800 (yld 1.83, wt 13.6% D20 + 2#/sx D42 + 5% | posed work). SEE RUL ion or recompletion. and reduced hole to 7-7/8'/8" hole to 12,550". 10# N-80 P-110 LT&C ca 10% D112 + 0.125#/sx D1 in with 600 sx PVL + 0. 3). Circulated 215 sx to | s. (Clearly state all perting E 19.15.7.14 NMAC. F "and resumed drilling d asing at 12,550". DV too 30 + 0.015g/sx D177 + 6 5% D112 + 30% D151 + pit. Cemented stage 2 w | nent details, and or Multiple Conditionally. KC of at 4793'. Floa 6% D20 + 2#/sx - 1.5% D174 + (ath 470 sx 35:65). Tailed in v | DP at 7642'. at collar at 12,457'. Ceme to D42 + 5% D44 + 0.2% D0.035g/sx D177 + 0.2% D0.0 | uding estimated date e diagram of ented stage 1 with 046 + 0.1% D800 46 + 0.5% D79 + 0.125#/sx D130 + 2% D13 (yld 1.33, |
| 13. Describe proposed of starting any proposed complete 2/11/11 – Dilled to 8546' a 2/20/11 – Reached TD 7-7/2/21/11 – Set 5-1/2" 17#, 2 625 sx 35:65:6 Poz "C" + 1 (yld 2.08, wt 12.6). Tailed 0.8% D800 (yld 1.83, wt 13.6% D20 + 2#/sx D42 + 5% wt 14.8). | posed work). SEE RUL ion or recompletion. Ind reduced hole to 7-7/8'/8" hole to 12,550'. Ind reduced hole to 7-7/8' Ind reduced hole to | s. (Clearly state all perting E 19.15.7.14 NMAC. F "and resumed drilling d asing at 12,550". DV too 30 + 0.015g/sx D177 + 6 5% D112 + 30% D151 + pit. Cemented stage 2 w 6% D800 (yld 2.08, wt 12) | nent details, and or Multiple Conditionally. KC of at 4793'. Floa 6% D20 + 2#/sx - 1.5% D174 + (ath 470 sx 35:65). Tailed in v | DP at 7642'. at collar at 12,457'. Ceme to D42 + 5% D44 + 0.2% D0.035g/sx D177 + 0.2% D0.0 | uding estimated date e diagram of ented stage 1 with 046 + 0.1% D800 46 + 0.5% D79 + 0.125#/sx D130 + 2% D13 (yld 1.33, |
| 13. Describe proposed of starting any proposed complete 2/11/11 – Dilled to 8546' a 2/20/11 – Reached TD 7-7/2/21/11 – Set 5-1/2" 17#, 2 625 sx 35:65:6 Poz "C" + 1 (yld 2.08, wt 12.6). Tailed 0.8% D800 (yld 1.83, wt 13.6% D20 + 2#/sx D42 + 5% wt 14.8). Spud Date: | posed work). SEE RUL ion or recompletion. Ind reduced hole to 7-7/8'/8" hole to 12,550'. Ind reduced hole to 7-7/8' | s. (Clearly state all perting E 19.15.7.14 NMAC. F "and resumed drilling desing at 12,550". DV too 30 + 0.015g/sx D177 + 65% D112 + 30% D151 + pit. Cemented stage 2 w W D800 (yld 2.08, wt 12) Rig Release Date: | nent details, and or Multiple Conditionally. KC of at 4793'. Floa 6% D20 + 2#/sx - 1.5% D174 + 0 ith 470 sx 35:65 (2.6). Tailed in v | I give pertinent dates, inclumpletions: Attach wellbord of the properties of the pro | uding estimated date e diagram of ented stage 1 with 046 + 0.1% D800 46 + 0.5% D79 + 0.125#/sx D130 + 2% D13 (yld 1.33, |
| 13. Describe proposed of starting any proposed complete 2/11/11 – Dilled to 8546' a 2/20/11 – Reached TD 7-7/2/21/11 – Set 5-1/2" 17#, 2 625 sx 35:65:6 Poz "C" + 1 (yld 2.08, wt 12.6). Tailed 0.8% D800 (yld 1.83, wt 13.6% D20 + 2#/sx D42 + 5% wt 14.8). | posed work). SEE RUL ion or recompletion. Ind reduced hole to 7-7/8'/8" hole to 12,550'. Ind reduced hole to 7-7/8' | s. (Clearly state all perting E 19.15.7.14 NMAC. F "and resumed drilling desing at 12,550". DV too 30 + 0.015g/sx D177 + 65% D112 + 30% D151 + pit. Cemented stage 2 w W D800 (yld 2.08, wt 12) Rig Release Date: | nent details, and or Multiple Conditionally. KC of at 4793'. Floa 6% D20 + 2#/sx - 1.5% D174 + 0 ith 470 sx 35:65 (2.6). Tailed in v | I give pertinent dates, inclumpletions: Attach wellbord of the properties of the pro | uding estimated date e diagram of ented stage 1 with 046 + 0.1% D800 46 + 0.5% D79 + 0.125#/sx D130 + 2% D13 (yld 1.33, |
| 13. Describe proposed of starting any proposed complete 2/11/11 – Dilled to 8546' a 2/20/11 – Reached TD 7-7/2/21/11 – Set 5-1/2" 17#, 2 625 sx 35:65:6 Poz "C" + 1 (yld 2.08, wt 12.6). Tailed 0.8% D800 (yld 1.83, wt 13.6% D20 + 2#/sx D42 + 5% wt 14.8). Spud Date: | posed work). SEE RUL ion or recompletion. Ind reduced hole to 7-7/8'/8" hole to 12,550'. Ind reduced hole to 7-7/8' | s. (Clearly state all perting E 19.15.7.14 NMAC. F "and resumed drilling desing at 12,550". DV too 30 + 0.015g/sx D177 + 15% D112 + 30% D151 + 15% D100 (yld 2.08, wt 12) Rig Release Date: | nent details, and or Multiple Condirectionally. KC of at 4793'. Flow 6% D20 + 2#/sx - 1.5% D174 + (ith 470 sx 35:65). Tailed in v | DP at 7642'. at collar at 12,457'. Ceme at D42 + 5% D44 + 0.2% D40.035g/sx D177 + 0.2% D40.035g/sx D177 + 0.2% D40.035g/sx D177 + 0.2% D40.035g/sx D177 + 0.2% D40.00000000000000000000000000000000000 | uding estimated date e diagram of Inted stage 1 with 046 + 0.1% D800 46 + 0.5% D79 + 0.125#/sx D130 + 2% D13 (yld 1.33, |
| 13. Describe proposed of starting any proproposed complete 2/11/11 – Dilled to 8546' a 2/20/11 – Reached TD 7-7/2/21/11 – Set 5-1/2" 17#, 2 625 sx 35:65:6 Poz "C" + 1 (yld 2.08, wt 12.6). Tailed 0.8% D800 (yld 1.83, wt 13 6% D20 + 2#/sx D42 + 5% wt 14.8). Spud Date: | posed work). SEE RULtion or recompletion. Ind reduced hole to 7-7/8'/8" hole to 12,550'. IOH N-80 P-110 LT&C cally D112 + 0.125#/sx D1 in with 600 sx PVL + 0.3). Circulated 215 sx to part of D44 + 0.2% D46 + 0.15 2/1/10 ormation above is true and other controls are controls and controls are controls are controls and controls are controls | s. (Clearly state all perting E 19.15.7.14 NMAC. F "and resumed drilling desing at 12,550". DV too 30 + 0.015g/sx D177 + 65% D112 + 30% D151 + 69it. Cemented stage 2 w W D800 (yld 2.08, wt 12) Rig Release Date: Rig Release Date: Rig Release Date: | nent details, and or Multiple Condirectionally. KC of at 4793'. Floa 6% D20 + 2#/sx - 1.5% D174 + (ith 470 sx 35:65 2.6). Tailed in v | I give pertinent dates, inclumpletions: Attach wellbord and the properties of the pr | uding estimated date e diagram of Inted stage 1 with 046 + 0.1% D800 46 + 0.5% D79 + 0.125#/sx D130 + 2% D13 (yld 1.33, |
| 13. Describe proposed of starting any proposed complete 2/11/11 – Dilled to 8546' a 2/20/11 – Reached TD 7-7/2/21/11 – Set 5-1/2" 17#, 2 625 sx 35:65:6 Poz "C" + 1 (yld 2.08, wt 12.6). Tailed 0.8% D800 (yld 1.83, wt 13.6% D20 + 2#/sx D42 + 5% wt 14.8). Spud Date: I hereby certify that the infection of the start of | posed work). SEE RULtion or recompletion. Ind reduced hole to 7-7/8'/8" hole to 12,550'. IOH N-80 P-110 LT&C cally D112 + 0.125#/sx D1 in with 600 sx PVL + 0.3). Circulated 215 sx to part of D44 + 0.2% D46 + 0.15 2/1/10 ormation above is true and other controls are controls and controls are controls are controls and controls are controls | s. (Clearly state all perting E 19.15.7.14 NMAC. F "and resumed drilling desing at 12,550". DV too 30 + 0.015g/sx D177 + 65% D112 + 30% D151 + 691. Cemented stage 2 w "My D800 (yld 2.08, wt 12) Rig Release Date: TITLE Regulatory | nent details, and or Multiple Condirectionally. KC of at 4793'. Flow 6% D20 + 2#/sx - 1.5% D174 + (ith 470 sx 35:65). Tailed in v | I give pertinent dates, inclumpletions: Attach wellbord at 1642'. At collar at 12,457'. Ceme at 242 + 5% D44 + 0.2% Discovery 20,035g/sx D177 + 0.2% Discovery 20,03 | uding estimated date e diagram of Inted stage 1 with 046 + 0.1% D800 46 + 0.5% D79 + 0.125#/sx D130 + 2% D13 (yld 1.33, |
| 13. Describe proposed of starting any proproposed complete 2/11/11 – Dilled to 8546' a 2/20/11 – Reached TD 7-7/2/21/11 – Set 5-1/2" 17#, 2 625 sx 35:65:6 Poz "C" + 1 (yld 2.08, wt 12.6). Tailed 0.8% D800 (yld 1.83, wt 13 6% D20 + 2#/sx D42 + 5% wt 14.8). Spud Date: | posed work). SEE RULtion or recompletion. Ind reduced hole to 7-7/8'/8" hole to 12,550'. IOH N-80 P-110 LT&C cally D112 + 0.125#/sx D1 in with 600 sx PVL + 0.3). Circulated 215 sx to part of D44 + 0.2% D46 + 0.15 2/1/10 ormation above is true and other controls are controls and controls are controls are controls and controls are controls | s. (Clearly state all perting E 19.15.7.14 NMAC. F "and resumed drilling desing at 12,550". DV too 30 + 0.015g/sx D177 + 65% D112 + 30% D151 + 69it. Cemented stage 2 w W D800 (yld 2.08, wt 12) Rig Release Date: Rig Release Date: Rig Release Date: | nent details, and or Multiple Condirectionally. KC of at 4793'. Floa 6% D20 + 2#/sx - 1.5% D174 + (ith 470 sx 35:65 2.6). Tailed in v | I give pertinent dates, inclumpletions: Attach wellbord at 1642'. At collar at 12,457'. Ceme at 242 + 5% D44 + 0.2% Discovery 20,035g/sx D177 + 0.2% Discovery 20,03 | uding estimated date e diagram of unted stage 1 with 046 + 0.1% D800 46 + 0.5% D79 + 0.125#/sx D130 + 2% D13 (yld 1.33, |
| 13. Describe proposed of starting any proposed complete 2/11/11 – Dilled to 8546' a 2/20/11 – Reached TD 7-7/2/21/11 – Set 5-1/2" 17#, 2 625 sx 35:65:6 Poz "C" + 1 (yld 2.08, wt 12.6). Tailed 0.8% D800 (yld 1.83, wt 13.6% D20 + 2#/sx D42 + 5% wt 14.8). Spud Date: I hereby certify that the infection of the start of | posed work). SEE RULtion or recompletion. Ind reduced hole to 7-7/8'/8" hole to 12,550'. IOH N-80 P-110 LT&C cally D112 + 0.125#/sx D1 in with 600 sx PVL + 0.3). Circulated 215 sx to part of D44 + 0.2% D46 + 0.15 2/1/10 ormation above is true and other controls are controls and controls are controls are controls and controls are controls | s. (Clearly state all perting E 19.15.7.14 NMAC. F "and resumed drilling desing at 12,550". DV too 30 + 0.015g/sx D177 + 65% D112 + 30% D151 + 69it. Cemented stage 2 w W D800 (yld 2.08, wt 12) Rig Release Date: Rig Release Date: Rig Release Date: | nent details, and or Multiple Condirectionally. KC of at 4793'. Floa 6% D20 + 2#/sx - 1.5% D174 + (ith 470 sx 35:652.6). Tailed in v | I give pertinent dates, inclumpletions: Attach wellbord of the properties of the pro | uding estimated date e diagram of unted stage 1 with 046 + 0.1% D800 46 + 0.5% D79 + 0.125#/sx D130 + 2% D13 (yld 1.33, |