

Submit 1 Copy To Appropriate District Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
October 13, 2009

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-015-37551
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. VO-7679
7. Lease Name or Unit Agreement Name Bebop BPE State <input checked="" type="checkbox"/>
8. Well Number 1H <input checked="" type="checkbox"/>
9. OGRID Number 025575 <input checked="" type="checkbox"/>
10. Pool name or Wildcat Avalon Shale

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator  
Yates Petroleum Corporation ☒

3. Address of Operator  
105 South Fourth Street, Artesia, NM 88210

4. Well Location  
Surface D : 660 feet from the North line and 330 feet from the West line  
BHL M : 330 feet from the South Line and 660 feet from the West line  
Section 36 Township 25S Range 31E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3313'GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☐


OTHER: ☐

OTHER: Surface casing ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

3/14/11 - Resumed drilling at 5:00 PM.

3/16/11 - TD 17-1/2" hole to 1076'. Set 13-3/8" 48# H-40 ST&C casing at 1076'. Cemented with 620 sx Class "C" + 0.125#/sx D130 + 3.76#/sx D20 + 0.94#/sx S001 + 0.188#/sx D46 (yld 1.97, wt 12.9). Tailed in with 200 sx Class "C" + 0.125#/sx D130 (yld 1.33, wt 14.8). Circulated 200 sx to pit. Tested casing to 600 psi for 30 min. WOC 36.75 hrs. Reduced hole to 12-1/4" and resumed drilling.



Spud Date:

1/31/11

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE March 24, 2011

Type or print name Tina Huerta E-mail address: tinah@yatespetroleum.com PHONE: 575-748-4168

For State Use Only

APPROVED BY: David Gray TITLE Field supervisor DATE 4-5-11

Conditions of Approval (if any):