Submit 3 Copies To Appropriate District Office	State of New Mexico		Form C-10			
<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240	Energy, Minerals and Natural Resources		WELL API NO.	<del>]4</del>		
District II	OIL CONSERVATION DIVISION		30-015-30729			
1301 W. Grand Ave., Artesia, NM 88210 District III	1220 South St. Francis Dr.		Indicate Type of Lease			
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, NM 87505		STATE FEE State Oil & Gas Lease No.	$\dashv$		
1220 S. St. Francis Dr., Santa Fe, NM 87505			State Off & Gas Lease No.			
SUNDRY NOT (DO NOT USE THIS FORM FOR PROPO	SUNDRY NOTICES AND REPORTS ON WELLS  NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A FERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH POSALS.)  Type of Well: Oil Well  Gas Well  Other					
COG Operating LLC			229137			
3. Address of Operator	N. 11 1 TW 70701		10. Pool name or Wildcat			
550 W. Texas Ave., Suite 100 Midland, TX 79701 Empire; Glorieta, Yeso 9610						
Well Location Unit Letter P:	990 feet from the Sou	th line and 9	990 feet from the East line			
		29E NMPM	County Eddy			
Section 19 Township 17S Range 29E NMPM County Eddy  11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3676 GR						
Pit or Below-grade Tank Application	Petros	70 GR				
Pit typeDepth to Grounds	waterDistance from nearest fres	h water well Dis	tance from nearest surface water			
Pit Liner Thickness: mil	Below-Grade Tank: Volume	bbls; Co	nstruction Material			
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data						
NOTICE OF INTENTION TO:  PERFORM REMEDIAL WORK   PLUG AND ABANDON   REMEDIAL WORK   ALTERING TEMPORARILY ABANDON   CHANGE PLANS   COMMENCE DRILLING OPNS.   P AND A PULL OR ALTER CASING   MULTIPLE COMPL   CASING/CEMENT JOB   DOWNHOLE COMMINGLE			☐ ALTERING CASING LING OPNS. ☐ P AND A			
OTHER:	Deepen 🛛	OTHER:				
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.						
See Attached procedure						
RECEIVED  APR 12 2011  NMOCD ARTESIA						
			TAIAIOOD LILLIES			
SIGNATURE Y CHA (	OUMTITLE	Regulatory An	alyst DATE 4/11/11	_		
Type or print name Netha A For State Use Only	aron E-mail address:	oaaron@conchoresou	* * 1			
APPROVED BY TO I Ald .	Man TITLE	Field Supervis	DATE 4-19-11			

Conditions of Approval (if any):

COG Operating, LLC State S 19 #12 API# 30-015-30729 P-19-17S-29E 990 FSL & 990 FEL Eddy Co, NM

## Deepening Procedure

- 1. MIRU rig.
- 2. Sqz upper Yeso w/ +/- 400 sx of Class C neat. Drill out squeeze.
- 3. PU 4-3/4" bit and drill 4-3/4" hole from 4218' to 5500'.
- 4. POOH w/ bit and drillstring.
- 5. RIH w/logs and log from TD to 3600'.
- 6. RIH w/ 4", 11.3# casing. See section 11 for general centralizer program.
- 7. Cement casing from TD to 4148' w/ 120 sxs Class C cmt. Drop plug and open DV tool. Circ cmt off DV tool. Drop plug to close DV tool.
- 8. PU workstring and RIH and drill out DV tool. POOH and LD workstring.
- 9. RDMO rig.

## **Completion Procedure**

- 1. MIRU rig.
- 2. RIH/ w/ perforating guns and perforate Yeso from 5100 5300 w/ 1 spf, 28 holes.
- 3. Acidize w/ 2500 gals of 15% HCl. Frac zone w/ 179,800 # of sand. Set plug at 5050'.
- 4. RIH w/ perforating guns and perforate Yeso from 4800' 5000'.
- 5. Acidize w/ 2500 gals of 15% HCl. Frac zone w/ 179,800 # of sand. Set plug at 4750'.
- 6. RIH w/ perforating guns and perforate Yeso from 4500' 4700'.
- 7. Acidize w/ 2500 gals of 15% HCl. Frac zone w/ 179,800 # of sand.
- 8. RIH and drill out plug at 4750' and 5050'.
- 9. RIH and cut or back off 4" casing at 4148'. POOH w/ 4" casing. Leave 4" liner from 4148' to 5500' (TD).
- 10. RIH w/ tbg and locate end of tbg at 4100'.
- 11. RIH w/ rods and pump.
- 12. RDMO rig.

SIZE A B C D E		35 33r1ë <sup>-</sup>	8"
F G DRIFT WELL NAME AND CENTRALIZED INTERCASING  F G DRIFT WELL NAME AND FOS 1/6 & MATERIAL 434 K 314 K 18" 6/85  MATERIAL 434 K 314 K 18" 6/85	RAY OIL TOOL CO.	ACCINCED  Solve  Bright  Bright  Control  Contro	