


Williams A Federal 6  
30-015-34200  
Lime Rock Resources A, L.P.  
May 2, 2011  
Conditions of Approval

1. Surface disturbance beyond the originally approved pad must have prior approval.
2. Closed loop system required.
3. A minimum of a 2000 (2M) BOP to be used. All blowout preventer (BOP) and related equipment (BOPE) shall comply with reasonable well control requirements. A two ram system with a blind ram and a pipe ram designed for the size of the work string shall be adequate. Tapered work strings will require an additional pipe ram. The manifold shall comply with Onshore Oil and Gas Order #2 Attachment I (2M Diagrams of Choke Manifold Equipment). The accumulator system shall have an immediately available power source to close the rams and retain 200 psi above pre-charge. The pre-charge test shall follow requirements in Onshore Order #2.
4. Submit subsequent sundry with details of work and current well test.
5. Work to be completed by October 31, 2011.

WWI 050211



NMOCD - Condition of Approval

Trucking companies being used to haul oilfield waste to disposal facilities - commercial or private - shall have an approved C-133 permit issued by NMOCD. A copy of this permit shall be available in each truck used to haul waste. It is the responsibility of the operator as well as the contractor to verify that this permit is in place. Drivers shall make this permit available upon request of an NMOCD inspector. Failure to comply will result in further action.

D. Gray 5-9-11