Submit 1 Copy To Appropriate District	State of New Mexico	Form C-103
Office District I	Energy, Minerals and Natural Reso	
1625 N. French Dr., Hobbs, NM 88240		WELL API NO.
District II	OIL CONSERVATION DIVIS	SION 30-005-60689 ~
1301 W. Grand Ave., Artesia, NM 88210 District III	1220 South St. Francis Dr.	5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410		STATE M FEE
District IV	Santa Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505		V-5650
part -	ICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
	SALS TO DRILL OR TO DEEPEN OR PLUG BACK	
	CATION FOR PERMIT" (FORM C-101) FOR SUCH	8. Well Number
PROPOSALS.)	Con Wall Dothon De A	1 ~
1. Type of Well: Oil Well	Gas Well Other P&A	
2. Name of Operator		9. OGRID Number 025575
Yates Petroleum Corporation  3. Address of Operator		025575 $\checkmark$ 10. Pool name or Wildcat
105 South Fourth Street, Artesia, NM 88210		Foor Ranch Pre-Perm, SW
	NVI 66210	Poor Ranch He-Felli, SW
4. Well Location	1000 6 6 4 2	
Unit Letter G :	1980 feet from the North line	and 1980 feet from the East line
Section 8	Township 10S Range	26E NMPM Chaves County
	11. Elevation (Show whether DR, RKB, R	PT, GR, etc.)
	3800' GR	
12 Check	Appropriate Box to Indicate Nature o	f Notice Report or Other Data
12. Check	appropriate Box to marcute reature o	rivolice, resport or other Bata
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:		
PERFORM REMEDIAL WORK	PLUG AND ABANDON REME	DIAL WORK ☐ ALTERING CASING ☐
TEMPORARILY ABANDON	CHANGE PLANS   COMM	MENCE DRILLING OPNS.□ P AND A □
PULL OR ALTER CASING		IG/CEMENT JOB
DOWNHOLE COMMINGLE	_	_
_		
OTHER:	OTHE	
		details, and give pertinent dates, including estimated date
		Iultiple Completions: Attach wellbore diagram of
proposed completion or re-	completion.	
5/4/11 - ND wellhead. NU we		
5/5/11 – Pumped 75 bbls brine down well. ND wellhead. NU BOP. Set CIBP at 6136'. Capped w/ 4 sx. Calculated TOC to be		
6097'. Set CIBP at 5924'. Capped w/ 4 sk cement. Calculated TOC to be 5885'.		
5/6/11 – Set CIBP at 5080'. Tagged CIBP.		
5/9/11 – Circulated salt gel. Tested casing to 500 psi. Spotted 25 sk "C" neat cement at 5080'. Calculated TOC to be 4833'.		
Spotted 25 sx "C" neat cement at 4466'. Calculated TOC to be 4219'		
5/10/11 – Perforated 4 holes at 2252'. Pressured to 600 psi. Spotted 25 sx "C" neat cement w/ 3% CaCl at 2302'. WOC 4 hours. Tagged at 2063'. Perforated 4 holes at 976'. Circulated out 8-5/8" X 5-1/2". Pumped 50 sx "C" neat cement. WOC.		
5/11/11 – Tagged plug at 753'. Perforated at 60'. Pumped down 5-1/2" and circulated out 8-5/8". Pumped 18 sx "C" neat cement.		
Cement to surface. ND BOP.	1 errorated at 60 . 1 diffeed down 3-1/2 and	d circulated out 6-5/8. Fulliped 18 8x. C. heat cement.
	f wellhead, and installed dry hole marker. F	filled cellar, cut anchors, and cleaned location.
WELL IS PLUGGED AND A		
	Approved for plugging of	well bore only. RECEIVED
	Liability under bond is ret	ained pending MAY 18 2011
	receipt of C-103 (Subsequ	
Spud Date:	Plugging) which may be for Page under forms. www.e	ound at OCD web
	, ago andor tormor trans-	mnrd.state.us/ocdNMOCD ARTESI
		_
I hereby certify that the information	above is true and complete to the best of my	v knowledge and belief
Thereby certify that the intermation	above is true and complete to the sest of my	, morreage una conor.
d ~ .		•
SIGNATURE	TITLE Regulatory C	Compliance Technician DATE May 17, 2011
	$\supset$	
Type or print nameCraig A	on E-mail addressreveaton	valespetroleum.com
For State Use Only	Liability under bi	uent Report of Well Plugging)
//\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	which may be for	and at OCD Web Page under
APPROVED BY	TITLE Forms, www.cmn	rd.state.nm.us/ocd. DATE 5/19/20//
Conditions of Approval (if any):		