

DISTRICT I
1626 N. French Dr., Hobbs, NM 88240

DISTRICT II
1301 W. Grand Avenue, Artesia, NM 88210

DISTRICT III
1000 Rio Higos Rd., Aztec, NM 87410

DISTRICT IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-102
Revised July 16, 2010

Submit one copy to appropriate
District Office

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, New Mexico 87505

WELL LOCATION AND ACREAGE DEDICATION PLAT

☐ AMENDED REPORT

API Number 30-015-39108	Pool Code 50270	Pool Name Penasco Draw; SA-Yeso (Assoc)
Property Code 38642	Property Name OKLAHOMA "32" FEE	Well Number 7
OGRID No. 162683	Operator Name CIMAREX ENERGY CO. OF COLORADO	Elevation 3393'

Surface Location

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
G	32	18 S	26 E		2310	NORTH	2310	EAST	EDDY

Bottom Hole Location If Different From Surface

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
Dedicated Acres 40		Joint or Infill		Consolidation Code		Order No.			

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

	<p>OPERATOR CERTIFICATION</p> <p>I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.</p> <p><i>Natalie Krueger</i> 6/7/2011 Signature Date</p> <p>Natalie Krueger Printed Name</p> <p>nkrueger@cimarex.com Email Address</p>
	<p>SURVEYOR CERTIFICATION</p> <p>I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.</p> <p><i>[Signature]</i> Date</p> <p><i>[Signature]</i> Signature</p> <p><i>[Seal]</i> Seal of Professional Surveyor</p> <p>24520 Certificate No.</p>
	<p>Certificate No. Gary L. Jones 7977</p>
	<p>BASIN SURVEYS 24520</p>

Mud, Casing, Cementing, and BOP Attachment
Oklahoma 32 Fee No. 7
 Cimarex Energy Co. of Colorado
 Unit G, Section 32
 T18S-R26E, Eddy County, NM

In response to questions asked under Section II B of Bulletin NTL-6, the following information is provided for your consideration:

Location: 2310 FNL & 2310 FEL

Elevation above sea level: 3393' GR

Proposed drilling depth: 3,000'

Proposed Mud Circulating System:

Depth	Mud Wt	Visc	Fluid Loss	Type Mud
0' to 950'	8.4 - 8.8	28	NC	FW
0' to 3000'	9.9 - 10.1	30-32	NC	Brine water

Sufficient mud materials will be kept on location at all times in order to combat lost circulation or unexpected kicks. In order to run DSTs, open hole logs, and casing, the viscosity and water loss may have to be adjusted in order to meet these needs.

Casing & Cementing Plan:

String	Hole Size	Depth	Casing OD	Weight	Collar	Grade
<i>Surface</i>	14¾"	0' to 950'	New 9¾"	36#	STC	J55
<i>Production</i>	8¾"	0' to 3000'	New 5½"	17#	LTC	N80

Cementing Plan:

Surface Lead Slurry: 870 sx Class "C" + 10% W-60 + 1% CaCl₂ + 0.25% R-38 + 5# Gilsonite per sx, 14.4 ppg, 1.56 cuft/sx, 7.04 gal/sx fw.

Tail Slurry: 330 sx Class C + 2% CaCl₂ + 0.25% R-38, 14.8 ppg, 1.35 cuft/sx, 6.34 gal/sx fw

TOC Surface

Production Lead Slurry: 380 sacks Class C 50/50 Poz + 10% Bentonite + 0.3% FL-10 + 0.25% R-38 + 5% Salt, Mixed at 11.92 ppg. Yeild 2.37 cuft/sx, 13.52 gal/sx Fresh Water

Tail Slurry: 260 sacks C Star Bond + 0.3% FL-10 + 0.1% C-20 + 0.25% R-38. Mixed at 13.2 ppg, Yeild 1.55 cuft/sx, 7.86 gal/sx Fresh Water

TOC Surface

Collapse Factor
1.125

Burst Factor
1.125

Tension Factor
1.6