

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT-" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Nearburg Producing Company

3. Address and Telephone No.

3300 N A t. Bldg. 2, Suite 120, Midland, Texas 79705

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

SHL 1977' FNL and 998' FWL, SEC 13, T22S, R24E  
BHL 850' FNL and 1650' FWL, SEC 13, T22S, R24E

5. Lease Designation and Serial No.  
NM12828

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

US 13 Federal # 1Y

9. API Well No.

30-015-24193

10. Field and Pool, or Exploratory Area

Undesignated-Cisco/Canyon

11. County or Parish, State

Eddy Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other \_\_\_\_\_

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form 1)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

9/18/00 TIH W/ 8 3/4 bit to 8,250' circ. well w/ mud

9/19/00 Spot 60 sks of cement @ 7521'-7332' Tagged @ 7332'

9/19/00 Spot 50 sks of cement @ 5000'-4842'

9/20/00 Spot 50 sks of cement @ 2910'-2810'

9/20/00 Set 9 5/8 CIBP @ 1520'

9/20/00 Spot 25 sks of cement @ 1520'-1446' Tagged @ 1446'

9/20/00 Spot 50 sks of cement @ 900'-751'

9/20/00 Spot 15 sks of cement @ 30'-surf.

Cut off wellhead & anchors 3' BGL. Install dry hole marker. Backfill & clean location

Approved as to plugging of the well bore.  
Liability under bond is retained until  
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed Kim Stearns  
(This space for Federal or State office use)

Title Regulatory Analyst

Date 10-18-00

Approved by \_\_\_\_\_  
Conditions of approval, if any:

Title PETROLEUM ENGINEER

Date OCT 19 2000