

RECEIVED

OCT 19 1972

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

NEW MEXICO OIL CONSERVATION COMMISSION
O.G.C.
ARTESIA, OFFICE

NO. OF COPIES RECEIVED	1
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K-4085
7. Unit Agreement Name
8. Farm or Lease Name AMOCO STATE
9. Well No. 1
10. Field and Pool, or Wildcat Wildcat
12. County Chaves

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> DRY HOLE
2. Name of Operator AZTEC OIL & GAS COMPANY
3. Address of Operator P. O. BOX 837, HOBBS, NEW MEXICO 88240
4. Location of Well UNIT LETTER P 660 FEET FROM THE South LINE AND 660 FEET FROM THE East LINE, SECTION 16 TOWNSHIP 8-S RANGE 29-E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3985.6 DF

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

It is proposed to plug this well in the following manner:

1. Set 100' cement plug at 2850-2950' (Slaughter).
2. Set 100' Cement plug at 1000-1100' (Yates).
3. Set 100' cement plug in and out of surface casing. (300-400')
4. Set 25' cement plug in top of surface casing.
5. Install proper marker, clear and level location.

(Verbal approval to set plugs 10-12-72.)

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Lester L. Duke* TITLE District Superintendent DATE Oct. 18, 1972

APPROVED BY *W.A. Gussard* TITLE OIL AND GAS INSPECTOR DATE OCT 20 1972

CONDITIONS OF APPROVAL, IF ANY: