| | The state of the state of the | Capy to SF |
|--|---|--|
| Form 9-331 (May 1963) | ED STATES SUBMIT IN TRIF AT DEPARTMENT OF THE INTERIOR verse side) | Form approved. Budget Bureau No. 42-R1424. |
| | GEOLOGICAL SURVEY | 5. LEASE DESIGNATION AND SERIAL NO. NM 0374460 |
| | SUNDRY NOTICES AND REPORTS ON WELLS | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME |
| (Do not | use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals CEIVE | |
| 1. OIL T | GAS [| 7. UNIT AGREEMENT NAME |
| 2. NAME OF OF | EBATOR JUN 1 1973 | 8. PARM OR LEASE NAME. |
| | Pennzoil Company 🗸 | McCrea Federal |
| 3. ADDRESS OF | P. O. Drawer 1828 - Midland, 本來來來來,可多不定是 | 9. WELL NO. |
| 4. LOCATION OF See also spe At surface | r WELL (Report location clearly and in accordance with any State requirements.* acc 17 below.) | 10. FIELD AND FOOL, OR WILDCAT |
| | 1980' FNL & 660' FEL of Sec. 20, T-9-S, R-26-E | Wildcat 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA |
| | | Sec. 20, T-9-S, R-26-E |
| 14. PERMIT NO. | 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3755 GR. | 12. COUNTY OR PARISH 13. STATE |
| 16. | Check Appropriate Box To Indicate Nature of Notice, Report, of | Chaves N. M. |
| | | EQUENT REPORT OF: |
| TEST WATI | R SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF | REPAIRING WELL |
| FRACTURE | | ALTERING CASING |
| SHOOT OR | | ABANDONMENT* |
| REPAIR WE | | operations X |
| (Other) | Completion or Reco | mpletion Report and Log form.) |
| proposed | work. If well is directionally drilled, give subsurface locations and measured and true ver his work.)* | tical depths for all markers and zones perti- |
| 4-23-73 | Spud 15" hole w/Cable tool rig. | 그는 그를 그림하는 그를 느르노이 💆 |
| 4-26-73 Ran 7jts. of 10 3/4", H-40, 40# casing & set @ 218'. Cement w/200 sx of Class "C" w/2% CaCl. Cement did not circulate. W.O.C. 8 hrs. Ran temperature | | |
| | <pre>survey, found cement top @ 70'. Ran 1" down outside 10 3/4" casing to 70'. Cement w/1</pre> | |
| | w/2% CaCl, circulate out 20 sx. W.O.C. 24 hrs. | |
| 4-28-73 | Drill 10" hole below 10 3/4" casing. | 변경 보고 변경 변경 변경 변경 보고 변경 변경 변경 변경 변경 변 |
| 5-11-73 Ran 859' of 8 5/8", J-55, 24# casing & mudded in to shut off water and | | but off water and |
| | hole sloughing. | |
| 6-04-73 | Perchad T.D. of 1 912! Day Comma Day Sidayall Navity | |
| 0-04-73 | Reached T.D. of 1,812'. Ran Gamma Ray-Sidewall Neutro T.D. to surface. | n Porosity log from and |
| | <u></u> | |
| | Prep to plug and abandon Dry hole. | Celwebii in Titi |
| | Hia | 1-71.73 as as 25 as 3 as |
| | | 그 그는 그 있을까워운 병기 등이라면 그 |
| | | CAMPA MARAES TO THE TOTAL OF TH |
| <u></u> | • | |
| 18. I hereby | rtify that the foregoing is true and correct TITLE Petroleum Engineer | DATE = 6-5-73 |
| (This pace | for Federal or State office DISTRICT ENGINEER | |
| APPROVEI | BY THILE | DATE 100- 81973 |
| CONDITIO | NS OF APPROVAL, IF ANY: | |