

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION
RECEIVED

DEC - 5 1973

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K 3764
7. Unit Agreement Name
8. Farm or Lease Name Allied State
9. Well No. 1
10. Field and Pool, or Wildcat Wildcat
12. County Chaves

SUNDRY NOTICES AND REPORTS ON WELLS ☐ C. C. ☒ O. C. C.
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DANGERED RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- 2. Name of Operator Pennzoil Company 3. Address of Operator P. O. Drawer 1828 - Midland, Texas 79701 4. Location of Well UNIT LETTER <u>G</u> , <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>33</u> TOWNSHIP <u>9-S</u> RANGE <u>26-E</u> NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 3774' G.L.
--

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11-28-73 Total depth 6,220'. Ran logs

11-29-73 Propose to plug and abandon as follows:

Set 35 sack cement plugs @ 5800-5900'	(Montoya)
" " " " " 4200-4300'	(Abo)
" " " " " 2000-2100'	(Glorieta)
" " " " " 1530-1630'	(Base of 8 5/8" csg. @ 1585')
Set 10 sack plug @ surface 0- 10'	

Cut off casing head & install marker. - All plugs will have 9.7# gal mud between them.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>J. Caney</u>	TITLE <u>Petroleum Engineer</u>	DATE <u>12-3-73</u>
APPROVED BY <u>W. A. Gussert</u>	TITLE <u>OIL AND GAS INSPECTOR</u>	DATE <u>DEC 5 1973</u>

CONDITIONS OF APPROVAL, IF ANY: