

Copy 65F e

N. M. O. O. CORY.

Form 9-531
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Follow instructions on re-
verse side)

Form approved.
Budget Project No. 42-31423.

5. LEASE DESIGNATION AND SERIAL NO.

Midwest Fed. 0223201

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR	8. FARM OR LEASE NAME
3. ADDRESS OF OPERATOR	Midwest Federal
4. LOCATION OF WELL (Report location of city and in accordance with any State requirements. See also space 17 below.) At surface	9. WELL NO.
1980' FSL, 660' FEL, Sec. 9, 14S, R 28 E,	3
10. FIELD AND POOL, OR WILDCAT	11. SEC. T., R., M., OR BLK. AND SURVEY OR AREA
11. SEC. T., R., M., OR BLK. AND SURVEY OR AREA	12. COUNTY OR PARISH
12. COUNTY OR PARISH	13. STATE
13. STATE	
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)
Oct. 15, 1973	3576.2 GR; 3586.2 KB
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data	

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

FILL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETION

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spot by tubing 20 sack plug across open hole. If pipe recovered below Queen sand at 1080' set 100 ft. plug across Queen formation. 25 pound of gel per barrel heavy mud will be spotted between these plugs. 100' plug across the base of the 8-5/8" surface pipe at 344'; 20 foot cement plug in the top of the surface pipe. 4 inch diameter by 4 feet above surface dry hole marker with well description and location.

RECEIVED
DEC - 3 1973
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Agent

DATE 11-27-1973

(This space for Federal or State office use)

TITLE

DATE

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

DEC 12 1973

U. S. GEOLOGICAL SURVEY
ARTESIA DISTRICT OFFICE

*See Instructions on Reverse Side