

Submit 3 Copies To Appropriate District Office

District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
811 South First, Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103

Revised March 25, 1999

TOIL CONSERVATION DIVISION

2040 South Pacheco  
Santa Fe, NM 87505

RECEIVED  
OCD - ARTESIA

WELL API NO.  
30005-60291

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

Twin Lakes San Andres Unit

7. Well No.

46

8. Pool name or Wildcat

Twin Lakes; San Andres (Assoc)

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☐ Other ☒

Injection

2. Name of Operator

Concho Oil & Gas Corp.

3. Address of Operator

110 W. Louisiana Ste 410; Midland, Tx 79701

4. Well Location

Unit Letter O : 330 Feet from the South line and 2310 feet from the East line

Section 36

Township 8S Range 28E

NMPM Chaves County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3846 GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: Perform MIT/Acidize/Return to Inj ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Concho Oil & Gas Corp. respectfully requests approval to perform a MIT/Acidize & return to injection the TLSAU No. 46 according to the following procedure:

1. Dig workover pit.
2. Run MIT.
3. Release pkr & tag bottom.
4. TOOH w/ tbq.
5. CO to PBTB w/ bit & bailer (if necessary).
6. Test tbq in hole & set pkr.
7. Run MIT.
8. Pump 500 gals Xylene, 10 bbls prod water w/ 5 gals TC 420 and 2 drums TC 405. Flush to top perf w/ prod wtr.
9. SI 12 hrs, minimum.
10. Swab & flow back load.
11. Acidize w/ 2000 gals 15% Pentol 300 and flush to top perf w/ prod wtr.
12. Flow & swab back all load wtr.
13. Return well to injection.

\* Notify N.M.O.C.D. To witness MIT.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Terri Statham TITLE Production Analyst DATE 5/2/01

Type or print name Terri Statham

Telephone No. 915/683-7443

(This space for State use)

APPROVED BY Mike Stillfield TITLE Envir. Eng. Spec. I DATE 5/14/2001