

COPIES RECEIVED	3
CONTRIBUTION	
FE	1
FILE	1 ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

JUN 28 1974

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

O.C.C.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator Coquina Oil Corporation ✓	8. Farm or Lease Name Jennings
3. Address of Operator 200 Bldg. of Southwest, Midland, Texas 79701	9. Well No. 1
4. Location of Well UNIT LETTER <u>G</u> , <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>32</u> TOWNSHIP <u>7S</u> RANGE <u>27E</u> NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) G.L. 4029'	12. County Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well @ 3:00 A.M., 6-20-74, and drilled 12 1/4" hole to 1,370 . Ran 32 jts. 24# J55 8rd ST&C 8 5/8" casing and set @ 1362.34. Cemented with 200 sxs. Howco Lite, plus 100 sxs. Class C with 2% calcium chloride and 1/4# Flocele in all cement. P. D. @ 4:30 A.M., 6-22-74. Cement did not circulate. Placed 6 yds. pea gravel around top of casing. WOC 23 hours. Tested 8 5/8" casing to 1000 psi. Held OK. Drilling 7 7/8" hole and preparing to drill ahead.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Diane C. F. [Signature] TITLE Engineer DATE 6-27-74

APPROVED BY [Signature] TITLE OIL AND GAS INSPECTOR DATE JUL 9 1974

CONDITIONS OF APPROVAL, IF ANY: