DISTRIBUTION	Supersede	s Old
	C-102 and	C-103
SANTA FE	NEW MEXICO OIL CONSERVATION COMMISSION Effective	1-1-65
FILE		vpe of Lease
U.S.G.S.		Fee
LAND OFFICE		
OPERATOR	JUL 9 1975 5. State OII 6 4239	Gas Lease No.
	42.39	
(DO NOT USE THIS FO	SUNDRY NOTICES AND REPORTS ON WELLS	
	7. Unit Agree	ment Name
OIL GAS		
WELL WEL WEL	8, Farm or Le	ase Name
	Stat	e
	nschutz Corporation	
. Address of Operator		
1270 E	Entex Building	Pool, or Wildcat
Location of Well		
UNIT LETTER	330 FEET FROM THE S LINE AND 1650 FEET FROM Wild	Lai
Fast	LINE, SECTION 32 TOWNSHIP 6-S RANGE 27-E NMPM.	
THE	LINE, SECTION TOWNSHIP RANGE	
mmmm	15. Elevation (Show whether DF, RT, GR, etc.) 12. County	
	4052 KB Chaves	
16.	Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTI	ICE OF INTENTION TO: SUBSEQUENT REPORT OF	DF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON . REMEDIAL WORK	TERING CASING
	COMMENCE DRILLING OPNS.	UG AND ABANDONMENT
TEMPORARILY ABANDON	CHANGE PLANS CASING TEST AND CEMENT JOB	
PULL OR ALTER CASING		
OTHER		
	Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date	e of starting any proposed
	Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date	e of starting any proposed
17. Describe Proposed or C work; SEE RULE 1103.	а.	
17. Describe Proposed or C work; SEE RULE 1103.	а.	
17. Describe Proposed or C work) SEE RULE 1103. 4-12-75 Spudd	ed	shoe to 75' by
17. Describe Proposed or C work) SEE RULE 1103. 4-12-75 Spudd 4-15-75 8-5/8	ed "24# K-55 ST&C casing was set at 1,399', was cemented from the	shoe to 75' by ad from 95' bac
17. Describe Proposed or C work) SEE RULE 1103. 4-12-75 Spudd 4-15-75 8-5/8 tempe to su	" ed " 24# K-55 ST&C casing was set at 1,399', was cemented from the rature survey, log attached. Surface casing annulus was cemente grface through 1" pipe w/55 sx of Class C cement. Primary cement	shoe to 75' by ad from 95' bac
17. Describe Proposed or C work) SEE RULE 1103. 4-12-75 Spudd 4-15-75 8-5/8 tempe to su	ed " 24# K-55 ST&C casing was set at 1,399', was cemented from the rature survey, log attached. Surface casing annulus was cemente urface through 1" pipe w/55 sx of Class C cement. Primary cement	shoe to 75' by ad from 95' bac
17. Describe Proposed or C work) SEE RUL E 1103. 4-12-75 Spudd 4-15-75 8-5/8 tempe to su +-150 4 16-75 Test	ed " 24# K-55 ST&C casing was set at 1,399', was cemented from the "rature survey, log attached. Surface casing annulus was cemente "rface through 1" pipe w/55 sx of Class C cement. Primary cement) sx CIC WOC 12 hrs. casing and BOP's to 1000 psi for 15 min - no pressure loss	shoe to 75' by ad from 95' bac
17. Describe Proposed or C work) SEE RUL E 1103. 4-12-75 Spudd 4-15-75 8-5/8 tempe to su +-150	ed " 24# K-55 ST&C casing was set at 1,399', was cemented from the grature survey, log attached. Surface casing annulus was cemente grface through 1" pipe w/55 sx of Class C cement. Primary cement) sx ClC WOC 12 hrs. casing and BOP's to 1000 psi for 15 min - no pressure loss Plug #1 6680-6580 w/35 sx Cl-H Mud 0.6 PPG 54 vis.	shoe to 75' by od from 95' bac
17. Describe Proposed or C work) SEE RUL E 1103. 4-12-75 Spudd 4-15-75 8-5/8 tempe to su +-150	ed " 24# K-55 ST&C casing was set at 1,399', was cemented from the rature survey, log attached. Surface casing annulus was cemente rface through 1" pipe w/55 sx of Class C cement. Primary cement) sx CIC WOC 12 hrs. casing and BOP's to 1000 psi for 15 min - no pressure loss Plug #1 6680-6580 w/35 sx C1-H Mud 0.6 PPG 54 vis.	shoe to 75' by od from 95' bac
17. Describe Proposed or C work) SEE RUL E 1103. 4-12-75 Spudd 4-15-75 8-5/8 tempe to su +-150 4 16-75 Test	ed "24# K-55 ST&C casing was set at 1,399', was cemented from the rature survey, log attached. Surface casing annulus was cemente rface through 1" pipe w/55 sx of Class C cement. Primary cement 0 sx CIC WOC 12 hrs. casing and BOP's to 1000 psi for 15 min - no pressure loss lug #1 6680-6580 w/35 sx C1-H Mud 0.6 PPG 54 vis. #2 5900-5800 w/" " " " " " " " "	shoe to 75' by ad from 95' bac
17. Describe Proposed or C work) SEE RUL E 1103. 4-12-75 Spudd 4-15-75 8-5/8 tempe to su +-150	ed "24# K-55 ST&C casing was set at 1,399', was cemented from the rature survey, log attached. Surface casing annulus was cementer inface through 1" pipe w/55 sx of Class C cement. Primary cement) sx CIC WOC 12 hrs. casing and BOP's to 1000 psi for 15 min - no pressure loss Plug #1 6680-6580 w/35 sx Cl-H Mud 0.6 PPG 54 vis. #2 5900-5800 w/" " " " " " " " " "	shoe to 75' by ad from 95' bac
17. Describe Proposed or C work) SEE RULE 1103. 4-12-75 Spudd 4-15-75 8-5/8 tempe to su +-150 4-16-75 Test 5-15-75 Set P	ed "24# K-55 ST&C casing was set at 1,399', was cemented from the rature survey, log attached. Surface casing annulus was cementer urface through 1" pipe w/55 sx of Class C cement. Primary cement sx CIC WOC 12 hrs. casing and BOP's to 1000 psi for 15 min - no pressure loss Plug #1 6680-6580 w/35 sx C1-H Mud 0.6 PPG 54 vis. #2 5900-5800 w/" " " " " " " " " #3 3969-3869 w/" " " " " " " " " "	shoe to 75' by ad from 95' bac
17. Describe Proposed or C work) SEE RULE 1103. 4-12-75 Spudd 4-15-75 8-5/8 tempe to su +-150 4-16-75 Test 5-15-75 Set P 5-17-75	<pre>% ed % 24# K-55 ST&C casing was set at 1,399', was cemented from the erature survey, log attached. Surface casing annulus was cemented inface through 1" pipe w/55 sx of Class C cement. Primary cement 0 sx C1C WOC 12 hrs. casing and BOP's to 1000 psi for 15 min - no pressure loss % Clug #1 6680-6580 w/35 sx C1-H Mud 0.6 PPG 54 vis. #2 5900-5800 w/" " " " " " " " #3 3969-3869 w/" " " " " " " " #4 1450-1350 w/" " " " " " " " #5 30' below ground to surface w/10 sx C1H cement</pre>	shoe to 75' by ad from 95' bac
17. Describe Proposed or C work) SEE RULE 1103. 4-12-75 Spudd 4-15-75 8-5/8 tempe to su +-150 4-16-75 Test 5-15-75 Set P	<pre>% ed % 24# K-55 ST&C casing was set at 1,399', was cemented from the grature survey, log attached. Surface casing annulus was cemented wrface through 1" pipe w/55 sx of Class C cement. Primary cement 0 sx ClC WOC 12 hrs. casing and BOP's to 1000 psi for 15 min - no pressure loss % lug #1 6680-6580 w/35 sx Cl-H Mud 0.6 PPG 54 vis. #2 5900-5800 w/" " " " " " " #3 3969-3869 w/" " " " " " " " #4 1450-1350 w/" " " " " " " " #5 30' below ground to surface w/10 sx ClH cement Set Dry Hole Marker</pre>	shoe to 75' by od from 95' bac
17. Describe Proposed or C work) SEE RULE 1103. 4-12-75 Spudd 4-15-75 8-5/8 tempe to su +-150 4-16-75 Test 5-15-75 Set P 5-17-75	<pre>% ed % 24# K-55 ST&C casing was set at 1,399', was cemented from the erature survey, log attached. Surface casing annulus was cemented inface through 1" pipe w/55 sx of Class C cement. Primary cement 0 sx C1C WOC 12 hrs. casing and BOP's to 1000 psi for 15 min - no pressure loss % Clug #1 6680-6580 w/35 sx C1-H Mud 0.6 PPG 54 vis. #2 5900-5800 w/" " " " " " " " #3 3969-3869 w/" " " " " " " " #4 1450-1350 w/" " " " " " " " #5 30' below ground to surface w/10 sx C1H cement</pre>	shoe to 75' by ad from 95' bac
17. Describe Proposed or C work) SEE RULE 1103. 4-12-75 Spudd 4-15-75 8-5/8 tempe to su +-150 4-16-75 Test 5-15-75 Set P 5-17-75 5-17-75	<pre>ed W 24# K-55 ST&C casing was set at 1,399', was cemented from the erature survey, log attached. Surface casing annulus was cemented inface through 1" pipe w/55 sx of Class C cement. Primary cement 0 sx C1C WOC 12 hrs. casing and BOP's to 1000 psi for 15 min - no pressure loss Plug #1 6680-6580 w/35 sx C1-H Mud 0.6 PPG 54 vis. #2 5900-5800 w/" " " " " " " " #3 3969-3869 w/" " " " " " " " #4 1450-1350 w/" " " " " " " " #5 30' below ground to surface w/10 sx C1H cement Set Dry Hole Marker Cleaned up leveled location, fenced reserve pit.</pre>	shoe to 75' by ad from 95' bac
17. Describe Proposed or C work) SEE RUL E 1103. 4-12-75 Spudd 4-15-75 8-5/8 tempe to su +-150 4-16-75 Test 5-15-75 Set P 5-17-75 5-17-75	<pre>ed W 24# K-55 ST&C casing was set at 1,399', was cemented from the erature survey, log attached. Surface casing annulus was cemented inface through 1" pipe w/55 sx of Class C cement. Primary cement 0 sx C1C WOC 12 hrs. casing and BOP's to 1000 psi for 15 min - no pressure loss Plug #1 6680-6580 w/35 sx C1-H Mud 0.6 PPG 54 vis. #2 5900-5800 w/" " " " " " " " #3 3969-3869 w/" " " " " " " " #4 1450-1350 w/" " " " " " " " #5 30' below ground to surface w/10 sx C1H cement Set Dry Hole Marker Cleaned up leveled location, fenced reserve pit.</pre>	shoe to 75' by od from 95' bac
17. Describe Proposed or C work) SEE RUL E 1103. 4-12-75 Spudd 4-15-75 8-5/8 tempe to su +-150 4-16-75 Test 5-15-75 Set P 5-17-75 5-17-75	<pre>% ed % 24# K-55 ST&C casing was set at 1,399', was cemented from the grature survey, log attached. Surface casing annulus was cemented wrface through 1" pipe w/55 sx of Class C cement. Primary cement 0 sx ClC WOC 12 hrs. casing and BOP's to 1000 psi for 15 min - no pressure loss % lug #1 6680-6580 w/35 sx Cl-H Mud 0.6 PPG 54 vis. #2 5900-5800 w/" " " " " " " #3 3969-3869 w/" " " " " " " " #4 1450-1350 w/" " " " " " " " #5 30' below ground to surface w/10 sx ClH cement Set Dry Hole Marker</pre>	shoe to 75' by od from 95' bac
17. Describe Proposed or C work) SEE RUL E 1103. 4-12-75 Spudd 4-15-75 8-5/8 tempe to su +-150 4-16-75 Test 5-15-75 Set P 5-17-75 5-17-75	<pre>ed W 24# K-55 ST&C casing was set at 1,399', was cemented from the wrature survey, log attached. Surface casing annulus was cemented wrface through 1" pipe w/55 sx of Class C cement. Primary cement 0 sx ClC WOC 12 hrs. casing and BOP's to 1000 psi for 15 min - no pressure loss Plug #1 6680-6580 w/35 sx Cl-H Mud 0.6 PPG 54 vis. #2 5900-5800 w/" " " " " " " " #3 3969-3869 w/" " " " " " " " #4 1450-1350 w/" " " " " " " " #5 30' below ground to surface w/10 sx ClH cement Set Dry Hole Marker Cleaned up leveled location, fenced reserve pit. Schlumberger - Comp. Neutron Form. Den. Log Attached.</pre>	shoe to 75' by ad from 95' bac
17. Describe Proposed or C work) SEE RULE 1103. 4-12-75 Spudd 4-15-75 8-5/8 tempe to su +-150 4-16-75 Test 5-15-75 Set P 5-17-75 5-17-75	<pre>ed W 24# K-55 ST&C casing was set at 1,399', was cemented from the erature survey, log attached. Surface casing annulus was cemented inface through 1" pipe w/55 sx of Class C cement. Primary cement 0 sx C1C WOC 12 hrs. casing and BOP's to 1000 psi for 15 min - no pressure loss Plug #1 6680-6580 w/35 sx C1-H Mud 0.6 PPG 54 vis. #2 5900-5800 w/" " " " " " " " #3 3969-3869 w/" " " " " " " " #4 1450-1350 w/" " " " " " " " #5 30' below ground to surface w/10 sx C1H cement Set Dry Hole Marker Cleaned up leveled location, fenced reserve pit.</pre>	shoe to 75' by ad from 95' bac
17. Describe Proposed or C work) SEE RULE 1103. 4-12-75 Spudd 4-15-75 8-5/8 tempe to su +-150 4-16-75 Test 5-15-75 Set P 5-17-75 5-17-75	<pre>ed W 24# K-55 ST&C casing was set at 1,399', was cemented from the wrature survey, log attached. Surface casing annulus was cemented wrface through 1" pipe w/55 sx of Class C cement. Primary cement 0 sx ClC WOC 12 hrs. casing and BOP's to 1000 psi for 15 min - no pressure loss Plug #1 6680-6580 w/35 sx Cl-H Mud 0.6 PPG 54 vis. #2 5900-5800 w/" " " " " " " " #3 3969-3869 w/" " " " " " " " #4 1450-1350 w/" " " " " " " " #5 30' below ground to surface w/10 sx ClH cement Set Dry Hole Marker Cleaned up leveled location, fenced reserve pit. Schlumberger - Comp. Neutron Form. Den. Log Attached.</pre>	shoe to 75' by od from 95' bac
17. Describe Proposed or C work) SEE RULE 1103. 4-12-75 Spudd 4-15-75 8-5/8 tempe to su +-150 4-16-75 Test 5-15-75 Set P 5-17-75 5-17-75 6-6-75	<pre>ed " 24# K-55 ST&C casing was set at 1,399', was cemented from the rature survey, log attached. Surface casing annulus was cementer inface through 1" pipe w/55 sx of Class C cement. Primary cement 0 sx ClC WOC 12 hrs. casing and BOP's to 1000 psi for 15 min - no pressure loss Plug #1 6680-6580 w/35 sx Cl-H Mud 0.6 PPG 54 vis. #2 5900-5800 w/" " " " " " " #3 3969-3869 w/" " " " " " " #4 1450-1350 w/" " " " " " " " #5 30' below ground to surface w/10 sx ClH cement Set Dry Hole Marker Cleaned up leveled location, fenced reserve pit. Schlumberger - Comp. Neutron Form. Den. Log Attached.</pre>	shoe to 75' by od from 95' bac
17. Describe Proposed or C work) SEE RULE 1103. 4-12-75 Spudd 4-15-75 8-5/8 tempe to su +-150 4-16-75 Test 5-15-75 Set P 5-17-75 5-17-75 6-6-75	<pre>ed W 24# K-55 ST&C casing was set at 1,399', was cemented from the wrature survey, log attached. Surface casing annulus was cemented wrface through 1" pipe w/55 sx of Class C cement. Primary cement 0 sx ClC WOC 12 hrs. casing and BOP's to 1000 psi for 15 min - no pressure loss Plug #1 6680-6580 w/35 sx Cl-H Mud 0.6 PPG 54 vis. #2 5900-5800 w/" " " " " " " " #3 3969-3869 w/" " " " " " " " #4 1450-1350 w/" " " " " " " " #5 30' below ground to surface w/10 sx ClH cement Set Dry Hole Marker Cleaned up leveled location, fenced reserve pit. Schlumberger - Comp. Neutron Form. Den. Log Attached.</pre>	shoe to 75' by od from 95' bac
17. Describe Proposed or C work) SEE RULE 1103. 4-12-75 Spudd 4-15-75 8-5/8 tempe to su +-150 4-16-75 Test 5-15-75 Set P 5-17-75 5-17-75 6-6-75	<pre>ed " 24# K-55 ST&C casing was set at 1,399', was cemented from the mature survey, log attached. Surface casing annulus was cemented inface through 1" pipe w/55 sx of Class C cement. Primary cement) sx ClC WOC 12 hrs. casing and BOP's to 1000 psi for 15 min - no pressure loss lug #1 6680-6580 w/35 sx Cl-H Mud 0.6 PPG 54 vis. #2 5900-5800 w/" " " " " " " " " #3 3969-3869 w/" " " " " " " " " #4 1450-1350 w/" " " " " " " " " #5 30' below ground to surface w/10 sx ClH cement Set Dry Hole Marker Cleaned up leveled location, fenced reserve pit. Schlumberger - Comp. Neutron Form. Den. Log Attached.</pre>	shoe to 75' by ed from 95' bac t 285 sx Hall.
17. Describe Proposed or C work) SEE RULE 1103. 4-12-75 Spudd 4-15-75 8-5/8 tempe to su +-150 4-16-75 Test 5-15-75 Set P 5-17-75 5-17-75 6-6-75 18. I hereby certify that the	<pre>ed " 24# K-55 ST&C casing was set at 1,399', was cemented from the mature survey, log attached. Surface casing annulus was cemented inface through 1" pipe w/55 sx of Class C cement. Primary cement) sx ClC WOC 12 hrs. casing and BOP's to 1000 psi for 15 min - no pressure loss lug #1 6680-6580 w/35 sx Cl-H Mud 0.6 PPG 54 vis. #2 5900-5800 w/" " " " " " " " " #3 3969-3869 w/" " " " " " " " " #4 1450-1350 w/" " " " " " " " " #5 30' below ground to surface w/10 sx ClH cement Set Dry Hole Marker Cleaned up leveled location, fenced reserve pit. Schlumberger - Comp. Neutron Form. Den. Log Attached.</pre>	shoe to 75' by od from 95' bac
17. Describe Proposed or C work) SEE RULE 1103. 4-12-75 Spudd 4-15-75 8-5/8 tempe to su +-150 4-16-75 Test 5-15-75 Set P 5-17-75 5-17-75 6-6-75	<pre>ed " 24# K-55 ST&C casing was set at 1,399', was cemented from the rature survey, log attached. Surface casing annulus was cementer inface through 1" pipe w/55 sx of Class C cement. Primary cement 0 sx ClC WOC 12 hrs. casing and BOP's to 1000 psi for 15 min - no pressure loss Plug #1 6680-6580 w/35 sx Cl-H Mud 0.6 PPG 54 vis. #2 5900-5800 w/" " " " " " " #3 3969-3869 w/" " " " " " " #4 1450-1350 w/" " " " " " " " #5 30' below ground to surface w/10 sx ClH cement Set Dry Hole Marker Cleaned up leveled location, fenced reserve pit. Schlumberger - Comp. Neutron Form. Den. Log Attached.</pre>	shoe to 75' by ed from 95' bac t 285 sx Hall.
17. Describe Proposed or C work) SEE RULE 1103. 4-12-75 Spudd 4-15-75 8-5/8 tempe to su +-150 4-16-75 Test 5-15-75 Set P 5-17-75 5-17-75 6-6-75 18. I hereby certify that the	<pre>ed " 24# K-55 ST&C casing was set at 1,399', was cemented from the mature survey, log attached. Surface casing annulus was cemented inface through 1" pipe w/55 sx of Class C cement. Primary cement) sx ClC WOC 12 hrs. casing and BOP's to 1000 psi for 15 min - no pressure loss "lug #1 6680-6580 w/35 sx Cl-H Mud 0.6 PPG 54 vis. #2 5900-5800 w/" " " " " " " " " #3 3969-3869 w/" " " " " " " " " #4 1450-1350 w/" " " " " " " " " #5 30' below ground to surface w/10 sx ClH cement Set Dry Hole Marker Cleaned up leveled location, fenced reserve pit. Schlumberger - Comp. Neutron Form. Den. Log Attached.</pre>	shoe to 75' by ed from 95' bac t 285 sx Hall.
17. Describe Proposed or C work) SEE RULE 1103. 4-12-75 Spudd 4-15-75 8-5/8 tempe to su +-150 4-16-75 Test 5-15-75 Set P 5-17-75 5-17-75 6-6-75 18. I hereby certify that the	<pre>ed " 24# K-55 ST&C casing was set at 1,399', was cemented from the mature survey, log attached. Surface casing annulus was cemented inface through 1" pipe w/55 sx of Class C cement. Primary cement) sx ClC WOC 12 hrs. casing and BOP's to 1000 psi for 15 min - no pressure loss "lug #1 6680-6580 w/35 sx Cl-H Mud 0.6 PPG 54 vis. #2 5900-5800 w/" " " " " " " " " #3 3969-3869 w/" " " " " " " " " #4 1450-1350 w/" " " " " " " " " #5 30' below ground to surface w/10 sx ClH cement Set Dry Hole Marker Cleaned up leveled location, fenced reserve pit. Schlumberger - Comp. Neutron Form. Den. Log Attached.</pre>	shoe to 75' by ed from 95' bac t 285 sx Hall.

2