	- N. M.	0. C. C. CUTI	Carry W SI
Form 9-331 May 1963)	U ED STATES DEPARTMENT OF THE INTE	SUBMIT IN TRI. ATE.	Form approved. Budget Bureau No. 42-R1 5. LEASE DESIGNATION AND SERIAL N
	GEOLOGICAL SURVEY		NM 0402600-A
	NDRY NOTICES AND REPORTS is form for proposals to drill or to deepen or plu Use "APPLICATION FOR PERMIT-" for suc		6 IF HUDTAN, ALLOUTSE OF TREE NA
I. OIL GAS WELL WELL	Dry Hole		7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR	llan Oil Concention		8. FARM OB LEASE NAME
PICUTE 3. ADDRESS OF OPERATO	llan Oil Corporation -		Butter Springs 9. WELL NO.
	Box 848, Roswell, New Mexico		<b>P</b> 2
<ol> <li>LOCATION OF WELL ( See also space 17 be At surface</li> </ol>	(Report location clearly and in accordance with a clow.)	· · · · · · · · · · · · · · · · · · ·	10. FIELD AND POOL, OR WILDCAT
	FNL & 990' FEL	APR 2 0 1976	WHALC         Jordan           11. SEC., T., R., M., OB BLK. AND         SUBVEY OR AREA
14. PERMIT NO.	1 15 FIEVATIONS (Show whathay	D. C. C.	Sec. 23-T14S-R28E 12. COUNTY OF PARISH 13. STATE
14. 2263011 NO.	3618 GL		Chaves New Mex
16.	Check Appropriate Box To Indicate	Nature of Notice, Report, or C	Other Data
	NOTICE OF INTENTION TO:	SUBSEQ	UENT REPORT OF:
TEST WATER SHUT-	OFF PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASING
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDONMENT* X
(Other)		(NOTE: Report results	s of multiple completion on Well letion Report and Log form.)
		est was P & A on 6/25/	
Set 10	DO' cement plugs 1870'-1970' 125' (Base of 8-5/8" casing),	(T.D.), 1260'-1360' (Q	ueen sand),
Set 10 325'-4	00' cement plugs 1870'-1970'	(T.D.), 1260'-1360' (Q 20 sx plug at surface	ueen sand),
Set 10 325'-4	00' cement plugs 1870'-1970' 125' (Base of 8-5/8" casing),	(T.D.), 1260'-1360' (Q 20 sx plug at surface	ueen sand), , to original state.
Set 10 325'-4	00' cement plugs 1870'-1970' 125' (Base of 8-5/8" casing),	(T.D.), 1260'-1360' (Q 20 sx plug at surface	ueen sand), , to original state.
Set 10 325'-4	00' cement plugs 1870'-1970' 125' (Base of 8-5/8" casing),	(T.D.), 1260'-1360' (Q 20 sx plug at surface	ueen sand), , to original state.
Set 10 325'-4	00' cement plugs 1870'-1970' 125' (Base of 8-5/8" casing),	(T.D.), 1260'-1360' (Q 20 sx plug at surface	ueen sand), , to original state.
Set 10 325'-4	00' cement plugs 1870'-1970' 125' (Base of 8-5/8" casing),	(T.D.), 1260'-1360' (Q 20 sx plug at surface	ueen sand), , to original state.
Set 10 325'-4	00' cement plugs 1870'-1970' 125' (Base of 8-5/8" casing),	(T.D.), 1260'-1360' (Q 20 sx plug at surface	ueen sand), , to original state.
Set 10 325'-4	00' cement plugs 1870'-1970' 125' (Base of 8-5/8" casing),	(T.D.), 1260'-1360' (Q 20 sx plug at surface	ueen sand), , to original state.
Set 10 325'-4	00' cement plugs 1870'-1970' 125' (Base of 8-5/8" casing),	(T.D.), 1260'-1360' (Q 20 sx plug at surface	ueen sand), , to original state.
Set 10 325'-4	00' cement plugs 1870'-1970' 125' (Base of 8-5/8" casing),	(T.D.), 1260'-1360' (Q 20 sx plug at surface	ueen sand), , to original state.
Set 10 325'-4 Will f	00' cement plugs 1870'-1970' 125' (Base of 8-5/8" casing),	(T.D.), 1260'-1360' (Q 20 sx plug at surface	ueen sand), , to original state.
Set 10 325'-4 Will f	DO' cement plugs 1870'-1970' H25' (Base of 8-5/8" casing), Fill pits and restore locatio	(T.D.), 1260'-1360' (Q 20 sx plug at surface	ueen sand), , to original state.
Set 10 325'-4 Will f 18. I hereby certify tha SIGNED	DO' cement plugs 1870'-1970' 425' (Base of 8-5/8" casing), Fill pits and restore locatio at the foregoing is true and correct Pai-ΩΩΩΩ	(T.D.), 1260'-1360' (Q 20 sx plug at surface n, as near as possible	ueen sand), , to original state. , to original state. , to original state. , to original state.
Set 10 325'-4 Will f 18. I hereby certify tha SIGNED	DO' cement plugs 1870'-1970' 425' (Base of 8-5/8" casing), Fill pits and restore locatio at the foregoing is true and correct I.M.Collon TITLE deral or State office use) TITLE	(T.D.), 1260'-1360' (Q 20 sx plug at surface n, as near as possible	ueen sand), , to original state. RECENTED JUSCOLOGICALINE MILSON ANTESIA
Set 10 325'-4 Will f 18. I hereby certify tha SIGNED	DO' cement plugs 1870'-1970' 425' (Base of 8-5/8" casing), Fill pits and restore locatio at the foregoing is true and correct P.M.Collon TITLE deral or State office use)	(T.D.), 1260'-1360' (Q 20 sx plug at surface n, as near as possible	Leen sand), , to original state. , to original state.
Set 10 325'-4 Will f 18. I hereby certify tha SIGNED	DO' cement plugs 1870'-1970' 425' (Base of 8-5/8" casing), Fill pits and restore locatio at the foregoing is true and correct I.M.Collon TITLE deral or State office use) TITLE	(T.D.), 1260'-1360' (Q 20 sx plug at surface n, as near as possible	Leen sand), , to original state. , to original state.
Set 10 325'-4 Will f 18. I hereby certify tha SIGNED	DO' cement plugs 1870'-1970' 425' (Base of 8-5/8" casing), Fill pits and restore locatio At the foregoing is true and correct I.M.C.C.L. TITLE deral or State office use) APPROVAL IF ANY: *See Instruction	(T.D.), 1260'-1360' (Q 20 sx plug at surface n, as near as possible	ueen sand), , to original state. $\mathbf{RECENVER}_{SO}$