

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT TO: (Other instruct.  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0559993

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

McCrea Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 31-T9S-R26E

12. COUNTY OR PARISH

Chaves

13. STATE

New Mexico

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER Dry Hole

2. NAME OF OPERATOR

J. Penrod Toles and McClellan Oil Corporations

3. ADDRESS OF OPERATOR

Post Office Box 848, Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

660' FSL & 1980' FWL

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3707.48' GR

O.C.C.  
ARTESIA, OFFICE

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(Note: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

7/17/76: Pursuant to Notice of Intent and verbal instructions, this test was P&A as follows: Filled bottom of hole from 1385-1495' w/sand and gravel. 10 sx Calseal plug 1375-1385'. 5 sx (20') cement 1350-1375'. 7" casing knocked off at 995'. Cement plug set 950-1050'. Cement plug set 850-950'. Cement plug set 250-350'. Cement plug set at 35-135'. 15 sx plug at surface. Heavy mud was pumped between all plugs. Will install marker and restore location to near as original state as possible.

18. I hereby certify that the foregoing is true and correct

SIGNED

J. Penrod Toles

TITLE

Operator

DATE

7/18/76

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: