

NEW MEXICO	
LAND DEPARTMENT	
NO. OF COPIES RECEIVED	
DATE RECEIVED	
SANTA FE	
FILE	
U.S. OFF.	
LAND OFFICE	
UPGRATER	X

LAND CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-79

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

RECEIVED

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

JUN 19 1981

1. Name of Operator

UNION OIL COMPANY OF CALIFORNIA /

O. C. D.

7. Unit Agreement Name

BOSQUE SPRINGS

2. Address of Operator

P. O. BOX 671 MIDLAND, TEXAS

ARTESIA, OFFICE

8. Farm or Lease Name

1

4. Location of Well

UNIT LETTER D 660 FEET FROM THE North LINE AND 660' FEET FROM
THE West LINE, SECTION 34 TOWNSHIP 6-S RANGE 28-E N.M.P.M.

10. Field and Pool, or Wildcat

Wildcat SA

15. Elevation (Show whether DF, RT, GR, etc.)

3999.5' Gr

12. County

Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☒

OTHER ☐

OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

T.D. 2591' PBTB 2488'

Perfs. 2445' - 2476'

2513' - 2525' Squzd. W/60 sx.

Casing Record: 8-5/8" OD @ 321' W/125 sx
5-1/2" OD @ 2591' W/225 sx

10-15-80 MI RU DDPU Pulled R&P and 2-3/8" OD tubing.

10-16-80 Ran CI bridge plug on 2-3/8" OD tubing and set @ 2400'. Spotted plug #1 on top of bridge plug 2400' - 2316' W/10 sx Class "H" neat cmt. Laid down tubing and perforated 5-1/2" OD casing @ 375' W/2 SPF. Plug #2 cemented top of 5-1/2" OD casing from 375' to surface through perfs. in 5-1/2" OD casing and in 8-5/8" and 5-1/2" annulus W/100 sx Class "H" neat cement. Pumped 9.5# mud between plugs. Welded 1/2" plate on 8-5/8" OD surface casing, placed 4" x 4" dry hole marker per NMOC regulations.

WELL PLUGGED AND ABANDONED 10-16-80

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED J.R. Hughes TITLE Dist. Drlg. Supt. DATE 6-17-81

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: