

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.O.S.	
LAND OFFICE	
OPERATOR	1 X

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease

State ☐Fee ☐

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT DEPTH. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

RECEIVED

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator UNION OIL COMPANY OF CALIFORNIA	8. Farm or Lease Name BOSQUE SPRINGS
3. Address of Operator P. O. BOX 671 MIDLAND, TEXAS	9. Well No. 1
4. Location of Well UNIT LETTER <u>D</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>34</u> TOWNSHIP <u>6-S</u> RANGE <u>28-E</u> NMPM.	10. Field and Pool, or Wildcat Wildcat <u>SA</u>

15. Elevation (Show whether DF, RT, GR, etc.)

3999.5' Gr

12. County

Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐PLUG AND ABANDON ☐REMEDIAL WORK ☐ALTERING CASING ☐TEMPORARILY ABANDON ☐COMMENCE DRILLING OPNS. ☐PLUG AND ABANDONMENT ☒PULL OR ALTER CASING ☐CHANGE PLANS ☐CASING TEST AND CEMENT JOB ☐OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

T.D. 2591' PBTD 2488'

Perfs. 2445' - 2476'

2513' - 2525' Squzd. W/60 sx.

Casing Record: 8-5/8" OD @ 321' W/125 sx
5-1/2" OD @ 2591' W/225 sx

10-15-80 MI RU DDPU Pulled R&P and 2-3/8" OD tubing.

10-16-80 Ran CI bridge plug on 2-3/8" OD tubing and set @ 2400'. Spotted plug #1 on top of bridge plug 2400' - 2316' W/10 sx Class "H" neat cmt. Laid down tubing and perforated 5-1/2" OD casing @ 375' W/2 SPF. Plug #2 cemented top of 5-1/2" OD casing from 375' to surface through perfs. in 5-1/2" OD casing and in 8-5/8" and 5-1/2" annulus W/100 sx Class "H" neat cement. Pumped 9.5# mud between plugs. Welded 1/2" plate on 8-5/8" OD surface casing, placed 4" x 4' dry hole marker per NMOCC regulations.

WELL PLUGGED AND ABANDONED 10-16-80

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED J.R. HughesTITLE Dist. Drlg. Supt.DATE 6-17-81APPROVED BY Doris SheffieldTITLE OIL AND GAS INSPECTORDATE JUL 29 1981

CONDITIONS OF APPROVAL, IF ANY: