

DAYTON ENTERPRISES, INC. WILDCAT (Devonian): (12-27-76); 7500' RT; se sw Sec 1-7s-28e; 660' FSL, 1980' FWL WF
 1 Elkins-Stat
 A.P. 66-000-00-00
 Sec; 2-1/2 mi N/Elkins; Opr's Elev. 4049' GL; Contr/WEK Dril.;
 WELL HISTORY: Spud 4-1-77; 13-5/8" 245'/250 sx; 8-5/8" 1861'/620 sx; DST (PRMN)
 2502-2517', op 1 hr 30 mins, rec 611' mud + 130' sil G3MCW, 1 hr ISIP 963#, FP 257-440#,
 2 hr FSLP 900; DST (PRMN) 2694-2747', op 1 hr 30 mins, rec 35' mud, 1 hr 30 min
 2 hr FSLP 900; DST (PSLV) 6600-77', Pkr failed; DST (PSLV) 6602-77', Pkr failed; DST (PSLV)
 6607-82', op 1 hr 20 mins, GTS in 10 mins @ 110 MCFGPD, rec 1000' HO&CCM + 200' GCM, 1 hr ISIP 2409#, FP 410-621#,
 3 hr FSLP 2412; 5-1/2" 7203'/300 sx; Perf (PSLV) 7119-21'; Acid (7119-21') 500 gals; Did not rec id (7119-21'); PB
 to 6700; Perf (PSLV) 6700-13' w/12 shots; Acid (6700-13') 500 gals; Swbd 10 BF (10-12% oil) (6700-13'); Perf ()
 6669-74', 6677-76'; Acid (6669-76') 500 gals; Swbd 4 BFPH (15% Oil) (6669-76'); Sqzd 6669-78'; Perf () 6669-74';
 Acid (6669-74') 5000 gals; Swbd 2 BFPH (10% oil) (6669-74'); Ppg wtr (6669-74'); TD 7203', PBD 6764', TOP.