

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

**RECEIVED**  
 NEW MEXICO OIL CONSERVATION COMMISSION  
 MAY 9 1977  
 O. C. C.  
 ALBUQUERQUE OFFICE

Form C-103  
 Supersedes Old  
 C-102 and C-103  
 Effective 1-1-65

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name White Ranch
9. Well No. #4
10. Field and Pool, or Wildcat White Ranch-Siluro Dev.
12. County Chaves

**SUNDRY NOTICES AND REPORTS ON WELLS**  
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REOPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
 USE APPLICATION FOR PERMIT TO DRILL (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator  
Tom L. Ingram

3. Address of Operator  
P. O. Box 1757, Roswell, New Mexico, 88201

4. Location of Well  
UNIT LETTER A 660 FEET FROM THE North LINE AND 660 FEET FROM  
THE East LINE, SECTION 33 TOWNSHIP 11S RANGE 29E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)  
3780 DF

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Work performed 5/4/77

At a total depth of 8810' ran 8848.89' of 5½" (20 jts 17# N-80 Buttress (789.22' - threads off) and 197 jts 17# N-80 LT&C (8059.67') casing). Set at 8810' and cemented with 200 sx of Class H + 6/10 of 1° CFR2 and 8# of salt per sx. Plugged down at 1350.  
 Ran Temp Survey - Top of cement outside csg 7960.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Tom L. Ingram</u>	TITLE <u>Operator</u>	DATE <u>5/5/77</u>
APPROVED BY <u>W. A. Gressitt</u>	TITLE <u>SUPERVISOR, DISTRICT II</u>	DATE <u>MAY 9 1977</u>
CONDITIONS OF APPROVAL, IF ANY:		