

COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

DEC 12 1977

O.C.C.
ARTESIA, OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
2. Name of Operator YATES EXPLORATION CO., INC.	5. State Oil & Gas Lease No.
3. Address of Operator 9720 B Candelaria N. E., Albuquerque, New Mexico 87112	7. Unit Agreement Name --
4. Location of Well UNIT LETTER E 1680 FEET FROM THE north LINE AND 800 FEET FROM west 27 TOWNSHIP 9S RANGE 28E NMPM.	8. Farm or Lease Name Plains Radio
15. Elevation (Show whether DF, RT, GR, etc.) 3828 G. L.	9. Well No. 1
	10. Field and Pool, or Wildcat Wildcat
	12. County Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	Surface casing <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 12-1/4" hole 11/17/77 @ 7:00 a.m.

Set 391' of 20#, 8-5/8" casing; cemented w/125 sx. Class "C", 2% CaCl₂, 2% gel, tailed in with 150 sx. 2% CaCl₂; cement circulated to surface; WOC 12 hrs. Pressure tested casing to 500 psi for 30"; held ok.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ch. Randy TITLE Secretary DATE 12/8/77

APPROVED BY For Rep. J. C. ... TITLE SUPERVISOR, DISTRICT II DATE DEC 16 1977

CONDITIONS OF APPROVAL, IF ANY: