

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

NEW MEXICO OIL CONSERVATION COMMISSION

NEW MEXICO OIL CONSERVATION COMMISSION
ALBUQUERQUE, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator PLANT INC. ✓	8. Farm or Lease Name Wildcat 3H
3. Address of Operator P.O. Box 34414, Albuquerque, N.M. 87124	9. Well No. 1
4. Location of Well UNIT LETTER <u>W</u> , <u>34</u> FEET FROM THE <u>W</u> LINE AND <u>2410</u> FEET FROM THE <u>West</u> LINE, SECTION <u>42</u> TOWNSHIP <u>34</u> RANGE <u>2</u> NMPM.	10. Field and Pool, or Wildcat Wildcat 3H
15. Elevation (Show whether DF, RT, GR, etc.) 3900 ft.	12. County Cibola

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Well spudded 12-30-77 at 11:00 A.M.

1-12-78 1 in. 500 feet. at 3000 feet 1 1/4" casing to total depth.
Cemented with 315 lbs. of cement. Drilled out. Later that
day, cement circulated to surface.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. B. McCoy TITLE Agent DATE 2-14-78

APPROVED BY W. A. Sussett TITLE SUPERVISOR, DISTRICT II DATE FEB 17 1978

CONDITIONS OF APPROVAL, IF ANY: