Form 9–331	
form 9-331	GOPY. Form Approved.
Dec. 1973	Budget Bureau No. 42-R1424
UNITED STATES	5. LEASE NM-0223201
DEPARTMENT OF THE INTER GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS	ON WELLS 7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or reservoir, Use Form 9-331-C for such proposals.)	plug back to a different B. FARM OR LEASE NAME
	Midwest "A" Federal
well well other Dryhole	9. WELL NO.
2. NAME OF OPERATOR	10. FIELD OR WILDCAT NAME
AMOCO PRODUCTION COMPANY	Sams Ranch Grayburg
3. ADDRESS OF OPERATOR P.O. Drawer A Levelland, TX 793	
4. LOCATION OF WELL (REPORT LOCATION CLE	
below.) AT SURFACE:1980'FNL&1980'FEL, SEC	5 14 40 20
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NA REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3579 GR
REQUEST FOR APPROVAL TO: SUBSEQUE TEST WATER SHUT-OFF	NT REPORT OF: (NOTE: Report results of multiple completion or zone change on Form 9–330.) BLM
 17. DESCRIBE PROPOSED OR COMPLETED OPER including estimated date of starting any propo measured and true vertical depths for all marks PXA well using the following proc plug with 35' cement. Cut and put 	cedure. Set cast iron bridge plug 1600'. Cappe Illed 5½" casing at 300'. Filled hole with mud 350'-250'. Cut wellhead off 8-5/8" casing, wel
 17. DESCRIBE PROPOSED OR COMPLETED OPER including estimated date of starting any propo- measured and true vertical depths for all marks PXA well using the following proc plug with 35' cement. Cut and pu fluid. Spotted 100' cement plug cap. Will turn well over to BLM 	beed work. If well is directionally drilled, give subsurface locations and ers and zones pertinent to this work.)* cedure. Set cast iron bridge plug 1600'. Cappe alled 5½" casing at 300'. Filled hole with mud 350'-250'. Cut wellhead off 8-5/8" casing, wel for use as water well.
 17. DESCRIBE PROPOSED OR COMPLETED OPER including estimated date of starting any propo- measured and true vertical depths for all marks PXA well using the following proc plug with 35' cement. Cut and pu fluid. Spotted 100' cement plug cap. Will turn well over to BLM Subsurface Safety Valve: Manu. and Type 	beed work. If well is directionally drilled, give subsurface locations and ers and zones pertinent to this work.)* cedure. Set cast iron bridge plug 1600'. Cappe alled 5½" casing at 300'. Filled hole with mud 350'-250'. Cut wellhead off 8-5/8" casing, wel for use as water well. Set @Ft.
 17. DESCRIBE PROPOSED OR COMPLETED OPER including estimated date of starting any proport measured and true vertical depths for all marks? PXA well using the following procepting with 35' cement. Cut and put fluid. Spotted 100' cement plug cap. Will turn well over to BLM Subsurface Safety Valve: Manu. and Type	beed work. If well is directionally drilled, give subsurface locations and ers and zones pertinent to this work.)* cedure. Set cast iron bridge plug 1600'. Cappe alled 5½" casing at 300'. Filled hole with mud 350'-250'. Cut wellhead off 8-5/8" casing, wel for use as water well. Set @Ft.
 17. DESCRIBE PROPOSED OR COMPLETED OPER including estimated date of starting any proport measured and true vertical depths for all marks? PXA well using the following procepting with 35' cement. Cut and put fluid. Spotted 100' cement plug cap. Will turn well over to BLM Subsurface Safety Valve: Manu. and Type	Set @
 17. DESCRIBE PROPOSED OR COMPLETED OPER including estimated date of starting any proport measured and true vertical depths for all marks? PXA well using the following proceeding with 35' cement. Cut and put fluid. Spotted 100' cement plug cap. Will turn well over to BLM Subsurface Safety Valve: Manu. and Type	beed work. If well is directionally drilled, give subsurface locations and ers and zones pertinent to this work.)* cedure. Set cast iron bridge plug 1600'. Cappe alled 5½" casing at 300'. Filled hole with mud 350'-250'. Cut wellhead off 8-5/8" casing, wel for use as water well. Set @Ft.
 17. DESCRIBE PROPOSED OR COMPLETED OPER including estimated date of starting any proport measured and true vertical depths for all marks? PXA well using the following proceplug with 35' cement. Cut and put fluid. Spotted 100' cement plug cap. Will turn well over to BLM Subsurface Safety Valve: Manu. and Type	beed work. If well is directionally drilled, give subsurface locations and ers and zones pertinent to this work.)* cedure. Set cast iron bridge plug 1600'. Capped 11 ers and 5½" casing at 300'. Filled hole with mud 350'-250'. Cut wellhead off 8-5/8" casing, well for use as water well. for use as water well. Set @Ft. prrect Set @Ft. ce for Federal or State office write ER 10-24-78