

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1 ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

RECEIVED

MAR 16 1978

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL UP TO 100 FEET OR PLUG BACK TO A DIFFERENT DEPTH. USE APPLICATION FOR PERMIT TO DRILL (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

1. Name of Operator
The Eastland Oil Company ✓

2. Address of Operator
704 Western United Life Building, Midland, Texas 79701

3. Location of Well
UNIT LETTER **P** **660** FEET FROM THE **South** LINE AND **660** FEET FROM THE **East** LINE, SECTION **17** TOWNSHIP **4S** RANGE **26E** N.M.P.M.

15. Elevation (Show whether DF, RT, GR, etc.)
3768' GR

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
L-692

7. Unit Agreement Name

6. Farm or Lease Name
State "17"

9. Well No.
1

10. Field and Pool, or Wildcat
Wildcat SA

12. County
Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	
		OTHER <input type="checkbox"/>	

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

State "17" #1 was spudded by Fred Pool Drilling Company with 11" bit at 5:00 PM March 11, 1978. The hole was drilled to 258 feet in sand and shale. Casing consisting of 6 joints of 24#, J-55, 8-5/8" was set at 256 feet and cemented with 175 sacks Class C with 2% CaCl₂. Cement was in place at 11:15 am, March 12, 1978. Circulated out 40 sacks excess cement. Allowed cement to set 18 hours and nipples up. Drilled out at 8:00 am, March 13, 1978. Tested casing with 600 psi for 30 min. - o.k.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED George L. Keal TITLE Superintendent DATE 3/14/78

APPROVED BY Mike Williams TITLE OIL AND GAS INSPECTOR DATE MAR 17 1978

CONDITIONS OF APPROVAL, IF ANY: