

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>William R. Mason</u>		Lease <u>Stewart Community</u>		Well # <u>1</u>	
Location of Well	Unit <u>23.0.8</u> <u>23.7.0</u>	Section <u>29</u>	Township <u>11</u>	Range <u>25</u>	County <u>Chavez</u>
Drilling Contractor	<u>Leonard George</u>		Type of Equipment <u>Rotary Lariat 2-15-78</u>		

APPROVED CASING PROGRAM

Witness

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>12 1/4"</u>	<u>8 5/8"</u>	<u>24</u>		<u>850</u>	<u>air</u>
<u>6 1/2</u>	<u>4 1/2"</u>	<u>9.5</u>		<u>1000'</u>	<u>"</u>

Casing Data:

Surface 22 joints of 8 5/8 inch 24 # Grade J-55
(Approved) (Rejected)

Inspected by M.S. date 1-16-78

Cementing Program

Size of hole 12 1/4 Size of Casing 8 5/8 Sacks cement required 400

Type of Shoe used Pin Float collar used No Btm 3 jts welded yes

TD of hole 851' Set 863' Feet of 8 5/8 Inch 24 # Grade J-55

New-used csg. @ 863' with 400 sacks neat cement around shoe

+ sax additives

Plug down @ 12:15 (AM) (PM) Date 1-17-78

Cement circulated yes No. of Sacks 10 SKS

Cemented by Denton Witnessed by Mike Stubbfield

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks:

2-22-78

355X Aug

355X "

10 SX 11 surface