

MOCC COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN T
(Other instruc
verse side)LICATE*
on reForm approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

N M 13986

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Trigg - Fed

9. WELL NO.

1 Y

10. FIELD AND POOL, OR WILDCAT

Wildcat SA

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

26T-13S-R27E

12. COUNTY OR PARISH

Chaves

13. STATE

N Mex

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Mountain States Petro. Corp ✓

3. ADDRESS OF OPERATOR

P O Box 1936 Roswell, N Mex 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

660 FNL & 2320 FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3565 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4/20/78 TD 2240'.

As per verbal approval District Engineer 4/20/78.

We plan to place 25 sx plug in 4-1/2" open hole, back into 5-1/2" casing. Attempt to recover 5-1/2" above about 1350' (top San Andres). Place 25 sx plug in and out of 5-1/2" stub. 25 sx plug across base of 8-5/8" csg. (313' GR). 10 sx surface plug, with dry hole marker. Heavy mud will be used between plug.

RECEIVED

APR 24 1978

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

K.C. Haveran by rw

TITLE

Geologist

DATE

04/21/78

(This space for Federal or State office use)

APPROVED BY

J. C. Lara

TITLE

ACTING DISTRICT ENGINEER

DATE

MAY 24 1978

CONDITIONS OF APPROVAL, IF ANY: