

U. S. M. O. C. C. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐		RECEIVED JUL 21 1978 U. S. C. C. ARTESIA, OFFICE	
2. NAME OF OPERATOR DEPCO, Inc.		8. FARM OR LEASE NAME "B" Sundance Federal "B"	
3. ADDRESS OF OPERATOR 800 Central, Odessa, Texas 79761		9. WELL NO. 1	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface Unit Letter J, 1980' FS & EL, Sec. 11, T12S, R29E		10. FIELD AND POOL, OR WILDCAT Wildcat Miss.	
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3802.4 Gr.	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 11-12S-29E	
		12. COUNTY OR PARISH Chaves	13. STATE N. M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud @ 4:00 PM. 6-27-78. Drilled 17 1/2" hole to 315'. Ran 12 3/8" 48# csg. set @ 315'. Cemented w/350 sx. Class "C", 27% ca. cl., 1/4# Celo-Flakes, & 5# Gilsontite. Cement circulated. WOC 18 hrs. Tested casing @ 1000# for 30 minutes. OK.

Drilled 11" hole to 2279'. Ran 8 5/8" (2057' of 24#, 222' of 32#) set @ 2279'. Cemented w/1262 sx. Class "C" Lodense, w/2% ca. cl. 1/4#, Celo-Flakes, 8# salt followed by 200 sx. Class "C" w/2% ca. cl. Plug down @ 1:30 PM 7-3-78. Cement circulated. WOC 18 hrs. Tested csg. @ 1000# for 30 minutes. OK. Resumed drilling.

RECEIVED

JUL 17 1978

**U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO**

18. I hereby certify that the foregoing is true and correct

SIGNED

Albert R. Stall

D. R. Mason

TITLE

Chief Clerk

DATE

7-13-78

(This space for Federal or State office use)

(Orig. Sgd.) **ALBERT R. STALL**

APPROVED BY

TITLE

ACTING DISTRICT ENGINEER

DATE

JUL 19 1978

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depth (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting to any casing; inner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.