

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

RECEIVED
 NEW MEXICO OIL CONSERVATION COMMISSION
 OCT 5 1978
 O. C. C.
 ARTESIA, OFFICE

Form C-103
 Supersedes Old
 C-102 and C-103
 Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. L-6998

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation ✓	8. Farm or Lease Name Smith JR State Com
3. Address of Operator 207 South 4th Street - Artesia, NM 88210	9. Well No. 1
4. Location of Well UNIT LETTER <u>L</u> , <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>14</u> TOWNSHIP <u>9S</u> RANGE <u>26E</u> NMPM.	10. Field and Pool, or Wildcat Wildcat Devonian
15. Elevation (Show whether DF, RT, CR, etc.) 3807' GR	12. County Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
 NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/> Set Production casing

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 6457'; WLPBTD 6433'. Ran 155 joints of 4½" K-55 10.5# of casing (6461') set at 6457'. Guide shoe at 6457', Diff-fill collar at 6416'. Used 7 centralizers. Cemented as follows: 450 sacks of Howco Lite, 5#/sack gilsonite, 3/10% CFR-2, 3#/sack KCL. Tailed in w/100 sacks of Class "C" 3/10% CFR-2, 3#/sack KCL. PD 7:16 AM 8-24-78. WOC 6 hours and ran Temperature Survey and found top of cement at 4100. WLPBTD 6433'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Lynne TITLE Geol. Secty DATE 10-5-78

APPROVED BY W. J. Gussert TITLE SUPERVISOR, DISTRICT II DATE OCT 6 1978

CONDITIONS OF APPROVAL, IF ANY:

