

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

SEP 11 1978

O. C. C.
ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>	
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name Faircloth	
9. Well No. 1	
10. Field and Pool, or Wildcat Wildcat	
12. County Chaves	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Hanagan Petroleum Corporation
3. Address of Operator P.O. Box 1737 - Roswell, New Mexico 88201
4. Location of Well UNIT LETTER M, 660 FEET FROM THE South LINE AND 660 FEET FROM THE West LINE, SECTION 29 TOWNSHIP 7S RANGE 27E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 4039 GR 4050 KB

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9/2/78 - Spud w/rotary tools 7:45 A.M. (Moranco Drilling Contractor)

9/3/78 - TD 300' - 8 jts. 13 3/8" 48# H40 St&c casing (308') in 17 1/2" hole. Set @ 300' cmt. Howco w/325 sx. Class "C" w/2% CaCl Plug Down 4:00 A.M. cement circ. drlg. plug 5:45 P.M. 9/3/78 WOC 12 hrs. Press up 600# for 30" no press drop.

9/4/78 - TD 1362', 11" hole, ran 34 jts. 8 5/8" 32# & 24# St&c csg. (1378'), Set @ 1362', cemented w/100 sx. Howco light @% CaCl + 200 sx. Class "C" 2% CaCl. Plug down 11:15 P.M., 9/4/78 WOC 18 hrs., 9/5/78 Drlg. plug @ 5:45 P.M. 9/5/78 Press up 1500#, 30" ok, no press. drop.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED M. L. Southerland TITLE Agent DATE 9/8/78

APPROVED BY For Record Only W. A. Lussert TITLE SUPERVISOR, DISTRICT II DATE SEP 12 1978

CONDITIONS OF APPROVAL, IF ANY: