

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn <u>6240</u>	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka <u>6600</u>	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates <u>340</u>	T. Miss <u>6790</u>	T. Cliff House _____	T. Leadville _____
T. 7 Rivers <u>500</u>	T. Devonian <u>7100</u>	T. Menefee _____	T. Madison _____
T. Queen <u>980</u>	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres <u>1490</u>	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzte _____
T. Glorieta <u>2880</u>	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock <u>3640</u>	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinebry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb <u>4300</u>	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo <u>5030</u>	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp <u>6030</u>	T. _____	T. Chinle _____	T. _____
T. Penn. _____	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn. "A" _____	T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	280	280	Cave in material from solado.	6670	6790		Atoka Lime & Shale
280	340	60	Tansill, Anhy.	6790	7095		Mississippian-Chert, Lime Green Shale
340	500	160	Yates, sand & shale	7095	7115		Silurian - White Dolo.
500	980	480	Seven Rivers, Anhy., Sd. & Shale				
980	1490	510	Grayburg - Queen, Anhy, Shale, salt & sand				
1490	1970	480	San Andres, Dolo, Salt Anhy & Shale				
1970	2880	910	San Andres - Dolo & Anhy				
2880	3640	760	Glorietta - Anhy, Sand, Salt & Shale				
3640	4300	660	Clearfork - Dolo & Anhy.				
4300	4590	290	Tubb Sand - Sand, Dolo & Anhy.				
4590	5030	440	Tubb - Anhy & Dolo				
5030	5600	570	Abo - Anhy, Dolo, Red & Green Shale				
5600	6030	430	Wichita Abo - Dolo & black Shale				
6030	6600	570	Wolfcamp - Penn. Lime, Chert & Black Shale				