

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 16093 *Copy to 57*

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposal.)

RECEIVED

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER

MAR 26 1979

2. NAME OF OPERATOR

Yates Petroleum Corporation ✓

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, NM 88210 ARTESIA, OFFICE

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FNL & 660' FEL of Section 23-14S -27E

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Phillips "KH" Fed.Com

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREASec. 23-14S-27E
Unit H NMPM

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3503' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Prod. Csg

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 8380' - Ran 242 joints of 4½" 11.6# & 10.5# K-55 ST&C casing as follows:
41 joints 11.6# (1720'), 190 joints 10.5# (6241') and 11 joints 11.6# (415')
(Total 8376') set at 8376'. 1-Guide shoe at 8376', Diff-Fill Collar at
8336'. Cemented w/250 gallons mud flush, 310 sacks Howco-Lite 2/10% Halad-
22 4/10% CFR-2, 5# KCL/sack, tailed in w/200 sacks Class H 2/10% Halad-22,
4/10% CFR-2, 5#KCL/sack. PD 4:53 AM 2-12-79. Tested to 1500#. OK.
Ran Temperature Survey and found top of cement at 6330'. WLPBTD 8320'.

RECEIVED

MAR 21 1979

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

*Christine Anderson*TITLE Geol. Secty.DATE 3-20-79

(This space for Federal or State office use)

APPROVED BY

*Joe S. Lara*TITLE ACTING DISTRICT ENGINEERDATE MAR 23 1979

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side