HO. OF COPIES AECEIVED		3	· · · · · · · · · · · · · · · · · · ·	Form C-103
DISTRIBUTION				Supersedes Old
ANTA FE	\Box		NEW MEXICO OIL CONSERVATION COMMISSION	C-102 and C-103 Effective 1-1-65
TILE	∇	$\mathbf{\nu}$	NEW MEXICO OIL CONSERVATION COMMISSION	
1.5.G.S.				Sa. Indicate Type of Lease
AND OFFICE			Minv 1 1070	State XX Fee
PERATOR	171		MAY 1 1979	5. State Oli & Gas Lease No.
			· · · · · · · · · · · · · · · · · · ·	LG-5247
(DO NOT USE THIS FO USE	SUI	NDR	Y NOTICES AND REPORTS ON WELLS ATTERIA OFFICE POSALS TO DRILL OR TO DEEPEN ON PLUG DACK TO A DIFFERENT AS OFFICE ON FOR PERMIT (FORM C-101) FOR SUCH PROPOSALS.)	
	. 🗆		0THER-	7. Unit Agreement Name
Name of Operator			/	8. Farm of Lease Name
Yates Petrol	Leur	n C	orporation 🖌	No. Coyote "KX" State
Address of Operator			,	9. Well No.
207 South Fo	our	Eh	Street - Artesia, NM 88210	1 1
Location of Well				10. Field and Pool, or Wildcat
UNIT LETTER M			660 FEET FROM THE South LINE AND 330 FEET FROM	Wildcat Eucer
			•	
West ,	-		N 10S RANGE NMPM.	
•••••				
	\square	\prod	15. Elevation (Show whether DF, RT, GR, etc.) 3739' GR	12. County Chaves
•	Che	ck A	ppropriate Box To Indicate Nature of Notice, Report or Oth	er Data
			TENTION TO:	
		••••		
ERFORM REMEDIAL WORK	ן		PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
EMPORARILY ABANDON	ĩ		COMMENCE DRILLING OPHS.	PLUG AND ABANDONMENT
ULL OR ALTER CASING	ๅี		CHANGE PLANS CASING TEST AND CEMENT JOB	FLOW AND ABANDONMENT
	-			· – – – – – – – – – – – – – – – – – – –
OTHER				

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 12" hole at 7:00 AM 4-4-79.

TD 250'. Ran 6 joints of 8-5/8" 24# K-55 (250') of casing set at 250'. I-guide shoe and 1 centralizer. Guide shoe at 250'. Centralizer at 60'. Cemented w/175 sacks of Class "C" 2% CaCl. PD 7:00 PM 4-21-79. Cement did not circulate. WOC and cement fell. Filled hole w/6 yards of Ready-Mix + 2% CaCl. WOC 18 hours. Reduced hole to 8". Drilled plug and tested to 600#, OK. Resumed drilling. Hit sulphur water at 280'. Have 50' of water in the hole and cannot bail down.

NED	Eddle In halful	Engineer	4-27-79
POVED BY	Wa Gresset	TITLE SUPERVISOR, DISTRICT II	MAY - 2 1979

NO. CY COPIES RECEIVED	_le					30-0	05-60552
DISTRIBUTION		NEW	NEXICO BIL CONSE	RYATHON COMMISSI	N	Form C-101	
ANTA FE	+					Revised 1-1-0	
.s.g.s. 2			MAR 1 5 19	70		SA. Indicate	Type of Lease
AND OFFICE			MAR 10 13	79			& Gas Lease No.
PERATOR /			~ ~ ~			LG-52	
<u> </u>						mm	
APPLICATIO	N FOR PE	RMIT TO I	ARTESIA, DEEPEN,	OR PLUG BACK			
Type of Work						7. Unit Agre	eement Name
				DL U			
I ype of well						8. Farm or L	
OIL X GAS WELL	0.7H)	ER		SINGLE M	ZONE	No. Co	yote "KX Stat
Name of Operator						9. Well No.	
Yates Petroleum Address of Operator	Corpor	ration	· · · · · · · · · · · · · · · · · · ·			1	,
•		7 *** * * *		10		10. Field or Wildca	nd Pool, or Wildcat
207 South 4th S			*****			WIIIICa	L.
UNIT LETTE	вМ	LOCA	TED 660 P	TEET FROM THE SOUT	th LINE		
D 330 FEET FROM	THE Wes	a t -	OF SEC. 29	WP. 105 RGE.	27E NMPM	AIIIIII	
D JJU FEET FROM	THE WE		OF SEC. 29	WP. LUS RGE. A	LIE NMPM	12. County	<u>,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,</u>
						Chave	es Alllllll
*******	HHHH	HHHH	******	<i>+++++++++++</i> +++++++++++++++++++++++++	++++++++	111111	
		///////			///////		
*************	HHHH	//////		19. Proposed Depth	19A. Formation		20. Rotary or C.T.
				pprox 975'	Queen		Cable Tools
. Elevations (Show whether DF,	RT, etc.)	21A. Kind &	Status Plug. Bond	21B. Drilling Contractor	L <u>aan de meeste e</u>	22. Approx	. Date Work will start
3739' GR		Blar	ıket			As so	on as possibl
•							
		PF	OPOSED CASING AND	CEMENT PROGRAM			
		r	ROPOSED CASING AND			·····	
SIZE OF HOLE	SIZE OF	CASING	WEIGHT PER FOOT	SETTING DEPT			EST. TOP
10"	8-5/	CASING	WEIGHT PER FOOT 24排	SETTING DEPT	Ready-	Mix	Circulate
		CASING	WEIGHT PER FOOT	SETTING DEPT		Mix	
10"	8-5/	CASING	WEIGHT PER FOOT 24排	SETTING DEPT	Ready-	Mix	Circulate
10" 8"	8-5/1 5½"	CASING 8"	WEIGHT PER FOOT 24# 14#	SETTING DEPT 125' 975'	Ready- 150 s	Mix x	Circulate Circulate
10" 8" Propose to dril	8-5/1 5날" 1 and	CASING 8" test th	WEIGHT PER FOOT 24# 14# ne Queen for	SETTING DEPT 125' 975' mation. Wi	Ready- 150 s	Mix x bout 1	Circulate Circulate 25' of
10" 8" Propose to dril	8-5/1 5날" 1 and	CASING 8" test th	WEIGHT PER FOOT 24# 14# ne Queen for	SETTING DEPT 125' 975' mation. Wi	Ready- 150 s	Mix x bout 1	Circulate Circulate 25' of
10" 8" Propose to dril	8-5/2 5½" 1 and 5	CASING 8" test the Quee	WEIGHT PER FOOT 24# 14# ne Queen for en is commer	mation. Will	Ready- 150 s 150 s 11 set a run 5½"	Mix x bout 1 casing	Circulate Circulate 25' of and circulat
10" 8" Propose to dril surface casing.	8-5/2 5½" 1 and 5	CASING 8" test the Quee	WEIGHT PER FOOT 24# 14# ne Queen for en is commer	mation. Will	Ready- 150 s 150 s 11 set a run 5½"	Mix x bout 1 casing	Circulate Circulate 25' of and circulat
10" 8" Propose to dril surface casing. the cement. Wi	8-5/3 5½" .1 and . . If t .11 per	CASING 8" test th he Quee forate	WEIGHT PER FOOT 24# 14# ne Queen for en is commer and stimula	mation. Wi cial, will a	Ready- 150 s 11 set a run 5½" d for pr	Mix x bout 1 casing	Circulate Circulate 25' of and circulat
10" 8" Propose to dril surface casing. the cement. Wi <u>Mud Progran:</u> N	8-5/3 5½" 1 and 5 If t 11 per	CASING 8" test th he Quee forate or FW (WEIGHT PER FOOT 24# 14# ne Queen for en is commer and stimula Gel if neede	mation. Will cial, will a te as needed	Ready- 150 s 150 s 11 set a run 5½" d for pr hole.	Mix x bout 1 casing oducti	Circulate Circulate 25' of and circulat on.
10" 8" Propose to dril surface casing. the cement. Wi <u>Mud Program:</u> N <u>BOP Program:</u> W	8-5/3 5½" I and If t Il per Native o	CASING 8" test th he Quee forate or FW (stall p	WEIGHT PER FOOT 24# 14# ne Queen for en is commer and stimula Gel if neede pressure-cor	mation. Will cmation. Will cial, will de as needed ed to clean h ntrol valve	Ready- 150 s 150 s 11 set a run 5½" d for pr hole. prior to	Mix x bout 1 casing oducti	Circulate Circulate 25' of and circulat on.
10" 8" Propose to dril surface casing. the cement. Wi <u>Mud Program:</u> N BOP Program: W	8-5/3 5½" I and If t Il per Native o	CASING 8" test th he Quee forate or FW (stall p	WEIGHT PER FOOT 24# 14# ne Queen for en is commer and stimula Gel if neede pressure-cor	mation. Will cial, will a te as needed	Ready- 150 s 11 set a run 5½" d for pr hole. prior to	Mix x bout 1 casing oducti drill	Circulate Circulate 25' of and circulat on. ing into
10" 8" Propose to dril surface casing. the cement. Wi <u>Mud Program:</u> N BOP Program: W	8-5/3 5½" I and If t Il per Native of	CASING 8" test th he Quee forate or FW (stall p	WEIGHT PER FOOT 24# 14# ne Queen for en is commer and stimula Gel if neede pressure-cor	mation. Will cmation. Will cial, will de as needed ed to clean h ntrol valve	Ready- 150 s 11 set a run 5½" d for pr hole. prior to t.	Mix x bout 1 casing oducti drill	Circulate Circulate 25' of and circulat on. ing into
10" 8" Propose to dril surface casing. the cement. Wi <u>Mud Program:</u> N BOP Program: W	8-5/3 5½" I and If t Il per Native of	CASING 8" test th he Quee forate or FW (stall p	WEIGHT PER FOOT 24# 14# ne Queen for en is commer and stimula Gel if neede pressure-cor	mation. Will cmation. Will cial, will de as needed ed to clean h ntrol valve	Ready- 150 s 150 s	Mix x bout 1 casing oducti drill PROVAL 7 90 DAYS (Circulate Circulate 25' of and circulat on. ing into AUD JNLESS
10" 8" Propose to dril surface casing. the cement. Wi <u>Mud Program:</u> N BOP Program: W	8-5/3 5½" I and If t Il per Native of	CASING 8" test th he Quee forate or FW (stall p	WEIGHT PER FOOT 24# 14# ne Queen for en is commer and stimula Gel if neede pressure-cor	mation. Will cmation. Will cial, will de as needed ed to clean h ntrol valve	Ready- 150 s 150 s	Mix x bout 1 casing oducti drill	Circulate Circulate 25' of and circulat on. ing into AUD JNLESS
10" 8" Propose to dril surface casing. the cement. Wi <u>Mud Program:</u> N <u>BOP Program:</u> W	8-5/3 5½" I and If t Il per Native of	CASING 8" test th he Quee forate or FW (stall p	WEIGHT PER FOOT 24# 14# ne Queen for en is commer and stimula Gel if neede pressure-cor	mation. Will cmation. Will cial, will de as needed ed to clean h ntrol valve	Ready- 150 s 150 s	Mix x bout 1 casing oducti drill PROVAL 7 90 DAYS (Circulate Circulate 25' of and circulat on. ing into AUD JNLESS
10" 8" Propose to dril surface casing. the cement. Wi <u>Mud Program:</u> N <u>BOP Program:</u> W	8-5/3 5½" I and If t Il per Native of	CASING 8" test th he Quee forate or FW (stall p	WEIGHT PER FOOT 24# 14# ne Queen for en is commer and stimula Gel if neede pressure-cor	mation. Will cmation. Will cial, will de as needed ed to clean h ntrol valve	Ready- 150 s 150 s	Mix x bout 1 casing oducti drill PROVAL 7 90 DAYS (Circulate Circulate 25' of and circulat on. ing into AUD JNLESS
10" 8" Propose to dril surface casing. the cement. Wi <u>Mud Program:</u> N <u>BOP Program:</u> W	8-5/3 5½" I and If t Il per Native of	CASING 8" test th he Quee forate or FW (stall p	WEIGHT PER FOOT 24# 14# ne Queen for en is commer and stimula Gel if neede pressure-cor	mation. Will cmation. Will cial, will de as needed ed to clean h ntrol valve	Ready- 150 s 150 s	Mix x bout 1 casing oducti drill PROVAL 7 90 DAYS (Circulate Circulate 25' of and circulat on. ing into AUD JNLESS
10" 8" Propose to dril surface casing. the cement. Wi <u>Mud Program:</u> N BOP Program: V	8-5/3 5½" I and If t 11 per Native Vill in the Que	CASING 8" test the he Quee forate or FW (stall p en form	WEIGHT PER FOOT 24# 14# ne Queen for en is commer and stimula Gel if neede pressure-cor nation at ab	mation. Wi control valve pout 900 fee	Ready- 150 s 150 s 11 set a run 5½" d for pr hole. prior to t. AF FOR DRILLA	Mix x bout 1 casing oducti oducti oducti oducti oducti oducti oducti oducti	Circulate Circulate 25' of and circulat on. ing into AUD JNLESS WENCED, 6/79
10" 8" Propose to dril surface casing. the cement. Wi <u>Mud Progran:</u> M <u>BOP Program:</u> W t	8-5/3 51/2" I and f If t Il per Native of Native of Native of Che Que	CASING 8" test the he Quee forate or FW (stall p en form	WEIGHT PER FOOT 24# 14# he Queen for en is commer and stimula Gel if neede pressure-cor nation at ak	mation. Wi mation. Wi cial, will : te as needed ed to clean i ntrol valve p bout 900 fee	Ready- 150 s 150 s 11 set a run 5½" d for pr hole. prior to t. AF FOR DRILLA	Mix x bout 1 casing oducti oducti oducti oducti oducti oducti oducti oducti	Circulate Circulate 25' of and circulat on. ing into AUD JNLESS WENCED, 6/79
10" 8" Propose to dril surface casing. the cement. Wi <u>Mud Progran:</u> M <u>BOP Program:</u> W t	8-5/3 51/2" I and f If t Il per Native of Native of Native of Che Que	CASING 8" test the he Quee forate or FW (stall p en form	WEIGHT PER FOOT 24# 14# he Queen for en is commer and stimula Gel if neede pressure-cor nation at ak	SETTING DEPT 125' 975' Imation. Will Scial, will Scial, will Ite as needed ed to clean htrol valve pout 900 feet Dr PLUG BACK, GIVE DATA npwledge and bellef.	Ready- 150 s 150 s 11 set a run 5½" d for pr hole. prior to t. AF FOR DRILLA	Mix x bout 1 casing oducti oducti odrill PROVAL 7 90 DAYS (NG COMM <u>6</u> 1	Circulate Circulate 25' of and circulat on. ing into ALID INLESS VENCED, 679 679
10" 8" Propose to dril surface casing the cement. Wi <u>Mud Progran:</u> M <u>BOP Program:</u> W t ABOVE SPACE DESCRIBE PR E ZONE. GIVE BLOWOUT PREVENT Breby certify that the information	8-5/3 51/2" I and f If t Il per Native of Native of Native of Che Que	CASING 8" test th he Quee forate or FW (stall g en form	WEIGHT PER FOOT 24# 14# he Queen for en is commer and stimula Gel if neede pressure-cor nation at ak	mation. Wi mation. Wi cial, will : te as needed ed to clean i ntrol valve p bout 900 fee	Ready- 150 s 150 s 11 set a run 5½" d for pr hole. prior to t. AF FOR PDRILLA EXPLRES.	Mix x bout 1 casing oducti oducti odrill PROVAL 7 90 DAYS (NG COMM <u>6</u> 1	Circulate Circulate 25' of and circulat on. ing into ALID JNLESS WENCED, 6/79
10" 8" Propose to dril surface casing the cement. Wi <u>Mud Progran:</u> M <u>BOP Program:</u> W t t ABOVE SPACE DESCRIBE PR E ZONE. GIVE BLOWOUT PREVENT ereby certify the the information	8-5/3 5½" I and If t Il per Native Vill in the Que	CASING 8" test th he Quee forate or FW (stall g en form	WEIGHT PER FOOT 24# 14# he Queen for en is commer and stimula Gel if neede pressure-cor nation at ak	SETTING DEPT 125' 975' Imation. Will Scial, will Scial, will Ite as needed ed to clean htrol valve pout 900 feet Dr PLUG BACK, GIVE DATA npwledge and bellef.	Ready- 150 s 150 s 11 set a run 5½" d for pr hole. prior to t. AF FOR PDRILLA EXPLRES.	Mix x bout 1 casing oducti drill PROVAL 7 90 DAYS (NG COMM <u>6</u>]	Circulate Circulate 25' of and circulat on. ing into ALID INLESS VENCED, 679 679
10" 8" Propose to dril surface casing. the cement. Wi <u>Mud Progran:</u> M <u>BOP Program:</u> W t t ABOVE SPACE DESCRIBE PR E ZONE. GIVE BLOWOUT PREVENT BOP Certify the the information ned	8-5/3 5½" I and If t Il per Native Vill in the Que	CASING 8" test th he Quee forate or FW (stall g en form	WEIGHT PER FOOT 24# 14# 14# ne Queen for en is commer and stimula Gel if neede pressure-cor nation at ak ROPOSAL IS TO DEEPEN C ete to the best of my k TiuleGec	SETTING DEPT 125' 975' mation. Will cial, will : ate as needed ed to clean b atrol valve p bout 900 feet PR PLUG BACK, GIVE DATA npwledge and belief. ol. Secty	Ready- 150 s 150 s 11 set a run 5½" d for pr hole. prior to t. AF FOR PDRILLA EXPLRES.	Mix x bout 1 casing oducti drill PROVAL 7 90 DAYS (NG COMM <u>6</u>]	Circulate Circulate 25' of and circulat on. ing into ALID INLESS VENCED, 679 679
10" 8" Propose to dril surface casing. the cement. Wi <u>Mud Progran:</u> M <u>BOP Program:</u> W t ABOVE SPACE DESCRIBE PR E ZONE. GIVE BLOWOUT PREVENT ereby certify the the information and <u>Untre</u>	8-5/3 5½" I and If t Il per Native Vill in the Que	CASING 8" test th he Quee forate or FW (stall g en form	WEIGHT PER FOOT 24# 14# 14# ne Queen for en is commer and stimula Gel if neede pressure-cor nation at ak ROPOSAL IS TO DEEPEN C ete to the best of my k TiuleGec	SETTING DEPT 125' 975' mation. Will cial, will : ate as needed ed to clean b atrol valve p bout 900 feet PR PLUG BACK, GIVE DATA npwledge and belief. ol. Secty	Ready- 150 s 150 s 11 set a run 5½" d for pr hole. prior to t. AF FOR PDRILLA EXPLRES.	Mix x bout 1 casing oducti o drill PROVAL 7 90 DAYS (NG COMM <u>6</u> 1 Date	Circulate Circulate 25' of and circulate on. ing into ALID JNLESS MENCED, 6/79 E AND PROPOSED NEW PRODUC 3-14-79
10" 8" Propose to dril surface casing. the cement. Wi <u>Mud Progran:</u> M <u>BOP Program:</u> W t t ABOVE SPACE DESCRIBE PR E ZONE. GIVE BLOWOUT PREVENT ereby certify the the information ned	8-5/3 5½" I and If t Il per Native Vill in the Que	CASING 8" test th he Quee forate or FW (stall g en form	WEIGHT PER FOOT 24# 14# 14# ne Queen for en is commer and stimula Gel if neede pressure-cor nation at ak ROPOSAL IS TO DEEPEN C ete to the best of my k TiuleGec	SETTING DEPT 125' 975' Imation. Will Scial, will Scial, will Ite as needed ed to clean htrol valve pout 900 feet Dr PLUG BACK, GIVE DATA npwledge and bellef.	Ready- 150 s 150 s 11 set a run 5 ¹ / ₂ " d for pr hole. prior to t. AF FOR PORILLA EXPLISES	Mix x bout 1 casing oducti o drill PROVAL 7 90 DAYS (NG COMM <u>6</u> 1 Date	Circulate Circulate 25' of and circulat on. ing into ALID INLESS VENCED, 679 679