

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESTA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Gates Petr Corp</i>		Lease <i>Erickson KY State</i>		Well # <i>1</i>	
Location of Well	Unit <i>1980N 6600E H</i>	Section <i>2</i>	Township <i>10</i>	Range <i>25</i>	County <i>Chavez</i>
Drilling Contractor	<i>L & M Drilling</i>		Type of Equipment <i>Rotary & start first work 5-14-79</i>		

* *Witness*

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>17 1/2"</i>	<i>13 7/8"</i>	<i>48</i>		<i>320</i>	<i>180 cins</i>
<i>12 1/4</i>	<i>8 5/8 or 9 5/8</i>	<i>24 or 32</i>		<i>900</i>	<i>600 "</i>
<i>8 3/4 or 7 7/8</i>	<i>5 1/2 or 4 1/2</i>	<i>15.5 or 10.5</i>		<i>5700</i>	<i>250 "</i>

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____

(Approved) (Rejected) _____

Inspected by _____ date _____

Cementing Program

Size of hole *12 1/4"* Size of Casing *8 5/8* Sacks cement required _____

Type of Shoe used *guide* Float collar used *inset* Btm 3 jts welded *No*

TD of hole *920'* Set *920'* Feet of *8 5/8* Inch *24* # Grade *J-SS*

New-used csg. @ *920'* with *100* sacks neat cement around shoe

+ *250* sack *Hall's 200* additives *1/4# floreal-10# gilsonite-290cc*

Plug down @ *3:00* (AM) (PM) Date *6/24/79*

Cement circulated *Yes* No. of Sacks *155x*

Cemented by *Halliburton* Witnessed by *Mike Stubblefield*

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____

No centralizers

lost circ @ 320' but regained

lost ddy @ 585'