

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRI  
(Other instruction  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM ~~0374460~~ NM26069

6. IF INDIAN, ALLOTTEE, OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Blakemore Federal

9. WELL NO.

#1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 20, T9S, R26E

12. COUNTY OR PARISH

Chaves

13. STATE

N. Mex.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

BOYD OPERATING COMPANY

3. ADDRESS OF OPERATOR

P. O. Box 1756, Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)

At surface

660 FNL, 660 FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3743.6 G.L.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

10/11/79 Depth 1576'. Ran Guidesheo, insert float, 3 centralizers, 2 baskets and 41 jts. of 24#, 8 5/8" csg. Landed @ 1564' G.L. Pumped 575 sx. Howco Lite cement w/10# gillsonite, 1/2 # flo-seal, 6# salt/sack and 200 sxs Class "C" neat cement 2.0% CaCl. Plug down 6:00 P.M. 10/10/79. Circ. 30 sx.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

President

DATE

10/15/79

(This space for Federal or State office use)

APPROVED BY

GEORGE H. STEWART

TITLE

DATE

OCT

CONDITIONS OF APPROVAL, IF ANY:

OCT 16 1979