

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>West Southern Petroleum Co.</i>		Lease <i>Christopher</i>		Well # <i>1</i>	
Location of Well	Unit <i>B</i> <i>330 N 2310E</i>	Section <i>32</i>	Township <i>6</i>	Range <i>26</i>	County <i>Chuska</i>
Drilling Contractor	<i>Rhymes Drilling Co.</i>		Type of Equipment <i>Rotary to start 9-20-79</i>		
* <i>Witness</i> APPROVED CASING PROGRAM					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>12"</i>	<i>8 7/8"</i>	<i>24</i>		<i>400</i>	<i>200 lbs.</i>
<i>7 7/8"</i>	<i>4 1/2"</i>	<i>10.5</i>		<i>1200</i>	<i>lbs.</i>
Casing Data:					
Surface _____ joints of _____ inch _____ # Grade _____					
(Approved) (Rejected) _____					
Inspected by _____ date _____					
Cementing Program					
Size of hole <i>11"</i> Size of Casing <i>8 5/8</i> Sacks cement required _____					
Type of Shoe used <i>guide</i> Float collar used <i>No</i> Btm 3 jts welded <i>yes</i>					
TD of hole <i>429'</i> Set <i>332'</i> Feet of <i>8 5/8</i> Inch <i>23</i> # Grade <i>K-SS</i>					
New-used csg. @ <i>332'</i> with <i>200</i> sacks neat cement around shoe					
+ _____ sack _____ additives <i>270cc</i>					
Plug down @ <i>2:30</i> (AM) (PM) Date <i>10/5/79</i>					
Cement circulated <i>No</i> No. of Sacks <i>0</i>					
Cemented by <i>W. H. Hinton</i> Witnessed by <i>BW Weaver</i>					
Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks: _____					

Wt @ 60' 240'-260'

*1 Ran 1" Tugged TOC @ 160'
pumped 150sx class C 270cc*
*2 Ran 1" Tugged TOC @ 40'
pumped 100sx class C 270cc
cement circulated. 10/6/79 M.S.*