

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.O.S.	
LAND OFFICE	
OPERATOR	1

DEC 12 1979

O. C. C.
ARTEZIA, OFFICE

5a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator STEVENS OIL COMPANY	8. Farm or Lease Name O'Brien "K"
3. Address of Operator P. O. Box 2203 - Roswell, New Mexico 88201	9. Well No. 3
4. Location of Well UNIT LETTER <u>K</u> , <u>1650</u> FEET FROM THE <u>South</u> LINE AND <u>1650</u> FEET FROM THE <u>West</u> LINE, SECTION <u>30</u> TOWNSHIP <u>8-S</u> RANGE <u>29-E</u> NMPM.	10. Field and Pool, or Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3948.8 Gr., 3954.8 KB	12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 11-03-79 Spud 11:30 p.m., drilled 121' and ran 121' 8-5/8" 20# surface casing; circulated cement w/75 sacks Class "C" cement. WOC
- 11-18-79 Ran 2870' 4-1/2" 9.5# casing and cemented with 225 sacks Dowell self-stress cement.
- 11-20-79 Perf. 2644, 45, 45.5, 46.5, 47, 47.5, 52.5, 53, 53.5, 54, 67, 67.5, 68, 86.5, 87, 87.5, 88.5, 89, 89.5, 90 w/1 spf.
- 11-21-79 Acidized perfs. w/6000 gal. 28% acid & ball sealers.
- 11-27-79 Re-perf. 2645, 47.5, 54, 54.5, 57.5, 58, 68, 71, 71.5, 86.5, 90.
- 11-28-79 Acidized w/10,000 gallons 28% acid.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Donald G. Hester TITLE Owner DATE 12-10-79

For Record Only
APPROVED BY W. A. Dresser TITLE SUPERVISOR, DISTRICT II DATE DEC 13 1979

CONDITIONS OF APPROVAL, IF ANY: