

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

JUL 20 1981

O. C. D.  
ARTESIA, OFFICE

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	11
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

5a. Indicate Type of Lease  
State ☐ Fee ☒  
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PUMP BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Ralph Nix	8. Firm or Lease Name Union Kerry
3. Address of Operator P.O. Box 617, Artesia, New Mexico 88210	9. Well No. #1
4. Location of Well UNIT LETTER H, 2310 FEET FROM THE North LINE AND 990 FEET FROM THE E LINE, SECTION 1, TOWNSHIP 8, RANGE 28, N.M.P.M.	10. Field and Pool, or Wildcat Bull's Eye San Andres
15. Elevation (Show whether DF, RT, GR, etc.) 4025' GR	12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- Set cast iron bridge plug at 2500' with a 35' cement cap. Tag plug.
- Cut and pull casing in the vicinity of 1500' size of cement plug will be determined as to the location of top of the Queen at 1452' and free point. Cement plug to be a minimum of 50' in and 50' out of the stub, however plug will be such as to sufficiently cover top of Queen also. Tag plug.  
Should it become necessary in the event free point is considerably higher than Queen, then addition to the above procedure a cast iron bridge plug inside the 4½ will be set at 1460' with a 35' cement cap. Tag plug.  
*100' Plug from 750-850*
- Set 100' cement plug from 200' to 300'. Tag plug.
- Set 15 sacks cement at surface.
- Install regulation dry hole marker.
- Proposed work to be completed as soon as well service unit is available. Dowell Well to engineer and supervise setting of plugs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ralph Nix TITLE \_\_\_\_\_ DATE July 13, 1981

APPROVED BY W. A. Gessert TITLE SUPERVISOR, DISTRICT II DATE JUL 21 1981

CONDITIONS OF APPROVAL, IF ANY:

Notify N.M.O.C.C. in sufficient time to witness

Plugging