

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.O.S.	
LAND OFFICE	
OPERATOR	1

5a. Indicate Type of Lease
State ☐ For ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

RECEIVED

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator

RALPH NIX

Address of Operator

P.O. Box 617, Artesia, New Mexico 88210

Location of Well

UNIT LETTER H 2310' FEET FROM THE North LINE AND 990' FEET FROM

THE East LINE, SECTION 1 TOWNSHIP 8S RANGE 28E N.M.P.M.

15. Elevation (Show whether DF, RT, GR, etc.)

4025' GL

7. Unit Agreement Name

8. Farm or Lease Name

UNION KERRY

9. Well No.

#1

10. Field and Pool, or wildcat

BULL'S EYE SAN ANDRES

12. County

Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☒

PULL OR ALTER CASING ☐

CHANGE PLANS ☐

CASING TEST AND CEMENT JOB ☐

OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8/17/81 Dia-Log Company ran GOI Bridge Plug in 4½" casing and set plug at 2500'.
Ran Dump Bailer with cement slurry to Bridge Plug.
Tag cement cap on Bridge Plug at 2460'.
Ran Jet Cutter and severed 4½" casing at 1830'

8/18/81 Pulled 4½" casing

8/19/81 Circulate with 120 bbls. water & gel.

Pumped 35 sx. Class H 2% SI cement from 1880' to 1780' - WOC 2 hrs.
Tagged at 1780'

Pumped 40 sx. Class H 2% SI Cement from 1500' to 1400' - WOC 2 hrs.
tagged plug at 1393'

Pumped 40 'sx. Class H 2% SI Cement from 850' to 750' - WOC 2 hrs.
Unable to tag.

(SEE ATTACHED PAGE FOR BALANCE OF DATA)

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED

TITLE

DATE

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

#17 Continued - Description of plugging operations.

8/19/81 Pumped 40 sx. Class H 2% SI Cement from 850' to 750' - WOC 2 hrs.
Tagged plug at 820'
Pumped 40 sx. Class H 2% SI from 820' to 730' - WOC 14 hrs.

8/20/81 Tagged plug at 785' OCC Rep. Approved.

Pumped 40 sx. Class H 2% SI Cement from 300' to 200' - WOC 2 hrs.
Tagged plug at 310', pumped 40 sx. Class H 2% SI from 300' to 200'
WOC 2 hrs. Tagged plug at 215' - OCC Rep. Approved.

Pumped 15 sx. Class H 2% SI cement for surface plug.

Installed Regulation Dry Hole Marker.