

Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

N M 10593

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

CHISUM FEDERAL

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

~~CHISUM FEDERAL~~ *San Andres*

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

K24 T11S R27E

12. COUNTY OR PARISH

CHAVES

13. STATE

NM

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

FI RO CORPORATION

3. ADDRESS OF OPERATOR

P.O. BOX 315 NATCHEZ MS. 39120

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

2279 FSL & 1660 FWL
UNIT K SEC 24 T11S R27E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3751

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6-15-80 SET 460 FT. & 5/8 CEMENTED W/100 SKS W/2% CaCL { HALLIBURTON }
6-30-80 DRILLED OUT CEMENT AND BAILED HOLE DRY { NO WATER ENTRY }
9-1-80 ~~DRILLED~~ SET 5 1/2 AT 2140 & CEMENTED W/175 SKS CLASS C { HALLIBURTON }
9-17-80 PERF 2043 TO 2090 W/4 SHOTS PER FT. { WELEX }
9-18-80 PUMP 1000 GAL. NE-FE ACID { HALLIBURTON }
10-6-80 PERF 2118 TO 2130 W/ 1 SHOT PER FT. { WELEX }
10-8-80 PUMP 4000 GAL ACID W/80200 SCF N2 {HALLIBURTON & NOWSCO }
FLOWED AND SWABBED WELL BACK AND SHUT DOWN TO MOVE RIG OFF
12-29-80 RAN 2 7/8 TUBING TO 2090 AND SET PUMPING UNIT AND TANK
1-2-80 START WELL TO PUMPING

RECEIVED
FEB 9 1981
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

John M. Hall

TITLE

***** PRESIDENT

DATE

2-3-81

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

FEB 10 1981

U.S. GEOLOGICAL SURVEY