

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 17037

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Five Mile Draw "LX" Fed.

9. WELL NO. Com

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Unit O, Sec. 34-6S-25E

12. COUNTY OR PARISH 13. STATE

Chaves

NM

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Yates Petroleum Corporation ✓

3. ADDRESS OF OPERATOR

207 S. 4th, Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

800' FSL & 2100' FEL, Sec. 34-6S-25E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3726' KB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐

(Other) TA Cisco & Produce Abo

PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Propose to temporarily abandon Cisco completion 4858-4865' by setting blanking plug in packer at 4600'. Sliding sleeve at approximately 4565' will be opened to allow Abo completion 3816-3836' to produce through tubing.

18. I hereby certify that the foregoing is true and correct

SIGNED

Albert R. Hall

TITLE

Engineer

DATE July 22, 1980

(This space for Federal or State office use)

APPROVED BY

(Signature)

TITLE

ACTING DISTRICT ENGINEER

DATE

JUL 25 1980

CONDITIONS OF APPROVAL, IF ANY:

DIAGRAMMATIC SKETCH of PROPOSED
DUAL COMPLETION

Elevation: 3726' KB (375 GL)

Spudded: 10-27-79

Completed: 12-6-79 (Penn)

Top of San Andres @ 423'

Top Giarreta @ 1090'

Top Abo @ 3519'

Top Wolfcamp @ 4180'

(2) Open sliding sleeve @ depth 4565'

(1) Install blanking plug in packer @ 4400'

Top Penn @ 4678'

Top pull RBP @ 4897'

(X)

800' ESL & 2,100' FEL

- Sec. 34, T. 6 S., R. 25 E., NMPM
Chaves County, N.M.

17 1/2" hole to 380'

13 3/8" 48" csg set @ 380', cement
to surface w/ 400sx.

12 1/4" hole to 1271'

8 7/8" 24" 55 csg set @ 1271', cement
to surface w/ 1,050sx.

Top of cement @ 3200' (Temp Survey)

} Abo Perfs 3564' - 3840'

Actual perfs 3816' - 3836'

Note: Penn completion may be temp abandoned
by setting a blanking plug in profile nipple in
packer @ 4400'. Sliding sleeve may be opened
to put Abo completion in tubing.

Sliding Sleeve in 2 3/8" Tbg @ about 4565'

2 3/8" Tubing in Packer @ 4400'

Perfs 4858' - 4865' (Penn)

4908' - 4916' Perfs (Penn)

PBD: 5101'

5 1/2" - 14 #/ft casing @ 5146' cement w/ 540sx

TD: 5150'