

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

RECEIVED

MAY 19 1980

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

O. C. D.  
ARTESIA, OFFICE

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
L-5242

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry Hole	7. Unit Agreement Name
2. Name of Operator	Willow Creek
Yates Petroleum Corporation ✓	8. Farm or Lease Name
3. Address of Operator	Willow Creek Unit
207 South 4th Street, Artesia, New Mexico 88210	9. Well No.
4. Location of Well	1
UNIT LETTER <u>G</u> , <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM	10. Field and Pool, or Wildcat
THE <u>East</u> LINE, SECTION <u>16</u> TOWNSHIP <u>4S</u> RANGE <u>25E</u> N.M.P.M.	Wildcat
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
3439.8' GR	Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 20' - 50' - 24" 13 3/8" - 362' - Circ. 8 5/8" - 1450' - 5 1/2" - 6230' - TOC above 1800'

Propose to freepoint, cut, and pull 5 1/2" casing (approximately 1800'). GIH and spot cement plugs through tubing as follows: 2000' - 2100' across perforations; from 50' inside and outside 5 1/2" casing stub (min 35 sx); 50' inside and outside 8 5/8" casing shoe (min. 35 sx). \* If 5 1/2" casing cut is close enough to 8 5/8" casing shoe, one plug from 50' inside 5 1/2" stub to 50' up into 8 5/8" shoe may be used. Heavy mud will be placed between plugs. Location will be cleaned and leveled with regulation abandonment marker set. Surface plug will be 25 sacks cement.

\* + Tag  
\* 35 SX 310-410

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Albert R. Hall TITLE Engineer DATE 5/16/80

APPROVED BY W. A. Gussert TITLE SUPERVISOR, DISTRICT II DATE MAY 20 1980

CONDITIONS OF APPROVAL, IF ANY:  
\* as noted above

Notify N.M.O.C.C. in sufficient time to

Plugging