

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN 1
(Other Instruc. s on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-36402 RECEIVED

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

MAY 12 1980

7. UNIT AGREEMENT NAME

O. C. D.

8. FEDERAL OFFICE

McClellan MB Fed.

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND

SURVEY OR AREA

Sec. 31-5S-25E

Unit L NMPM

12. COUNTY OR PARISH

Chaves

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	2. NAME OF OPERATOR Yates Petroleum Corporation	3. ADDRESS OF OPERATOR 207 South 4th Street - Artesia, NM	4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FSL & 660' FWL of Section 31-5S-25E	14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3856' GR
--	--	--	--	----------------	--

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

TD 4650'; PBTD 4174' -

WIH w/Steel Carrier Guns, Gubierson Uni VI packer on 2-7/8" tubing. Set packer at 3914'. Perforated 3930-3960' w/120 .50" holes (4spf) GTS in 1 hour, TSTM. Sand Frac'd perforations w/27150gallons of treated fluid. (20000g Tital II, 2000 g 15% spearhead acid and 5150 gallons CO-2); 60000# sand (50000# of sand and 10000# 100 mesh w/ball sealers. Well cleaned up and flowed 230# on 1/2" choke.

18. I hereby certify that the foregoing is true and correct

SIGNED

Christine Tomlinson

TITLE

Geol. Secty.

DATE

2-23-80

(This space for Federal or State office use)

194g. Sgd.) GEORGE H. STEWART

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DISTRICT ENGINEER

DATE

MAY 08 1980