

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.O.S.	
LAND OFFICE	
OPERATOR	1

RECEIVED

APR 14 1980

O. C. D.

3a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K-2114
7. Unit Agreement Name
8. Farm or Lease Name Plains State
9. Well No. 11
10. Field and Pool, or Wildcat E. Chisum, S.A.
12. County Chaves

SUNDRY NOTICES AND REPORTS ON WELLS ARTESIA, OFFICE  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Fred Pool Data. Co.
3. Address of Operator 409 White Bldg. Roswell, N.M. 88201
4. Location of Well UNIT LETTER H 2310 FEET FROM THE N LINE AND 330 FEET FROM THE E. LINE, SECTION 16 TOWNSHIP 11S RANGE 28E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3707.97 GL

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	
		Oil String <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Set 521 ft. of 7" casing-23#. Set in Anhydrite. Cemented, circulated  
W.O.C. 24 hrs. Pressured up to 500#, 30 minutes; no pressure drop.  
1-17-80

Set 2278' of 4 1/2" production casing 9.5#

Cemented with 170 sx 50/50 POZ- 4% Gel- 2% S-1

v Tail end w/ 150 sx 50/50 POZ. Cement did not circulate.

ADDITIONAL CEMENT INFORMATION- Filled annulus from 275' to surface w/  
6 cubic yards of neat cement slurry using 1" tubing run to 274'.

INTEND TO ACIDIZE AND PERFORATE.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Patti Hol James TITLE Secretary DATE 4-11-80

APPROVED BY W. G. Lussert TITLE SUPERVISOR, DISTRICT II DATE APR 15 1980

CONDITIONS OF APPROVAL, IF ANY: