

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TR. .CATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

USA-NM-10893

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Godfery MP Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat *Granite Wash*11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 10-7S-25E

Unit G NMPM

12. COUNTY OR PARISH

Chaves

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER ☐ JAN 21 1980

2. NAME OF OPERATOR Yates Petroleum Corporation O. C. D.

3. ADDRESS OF OPERATOR 207 South 4th Street - Artesia, NM 88210 ARTESIA OFFICE

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FNL & 1980' FEL of Section 10-7S-25E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3821' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded a 12½" hole at 12:00 noon 12-30-79.

Ran 10 joints of 10-3/4" 30# J-55 (400') of casing set at 400'. 1-guide shoe. Cemented w/275 sacks of Class C 4% CaCl. PD 2:30 AM 12-31-79. Circulated 10 sacks to surface. WOC 12 hours, backed off, reduced hole to 9½", drilled plug and tested to 600#. OK. Resumed drilling.

Ran 30 joints of 7" 20# J-55 (1314') of casing set at 1312'. Cemented w/200 sacks 50-50 Lite Poz C-3, 5#/sack Kolite, 1/4# celloflakes/sack, 2% CaCl. Followed w/100 sacks Class C 4% CaCl. PD 3:00 PM 1-2-80. Cement circulated 20 sacks to pit. WOC 18 hours. Nippled up and tested to 100# for 30 minutes. Reduced hole to 6½", drilled plug and tested to 600#. OK, resumed drilling.

RECEIVED

JAN 17 1980

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Geol. Secty

DATE 1-16-80

(This space for Federal or State office use)

APPROVED (Signature) GEORGE H. STEWART

TITLE

DATE

JAN 17 1980

CONDITIONS OF APPROVAL, IF ANY: